



## SAFETY DATA SHEET

### 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING  
**Product number** 425/G149/A/B/D  
**UFI** UFI: HKXP-W244-N00C-RQ4S

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** PAINT BASE FOR TINTING SYSTEM

##### 1.3. Details of the supplier of the safety data sheet

<b>Supplier</b>	TEAL & MACKRILL LIMITED Lockwood Street HULL UK HU2 OHN +441482320194 (T) +441482219266 (F) info@teamac.co.uk	TEAL AND MACKRILL EU B.V. Zandvoortstaat 69 1976 BN IJMUIDEN THE NETHERLANDS +441482320194 (T) +441482219266 (F) info@teamac.co.uk
<b>Contact person</b>	Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above	

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1482 320194 Teamac (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)  
**SDS No.** 11495

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 3 - H226  
**Health hazards** STOT SE 3 - H335, H336  
**Environmental hazards** Aquatic Chronic 2 - H411

##### 2.2. Label elements

###### Hazard pictograms



Signal word

Warning

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

<b>Hazard statements</b>	H226 Flammable liquid and vapour. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/ container in accordance with national regulations.
<b>Supplemental label information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>Contains</b>	HYDROCARBONS, C9, AROMATICS, HYDROCARBONS, C9-C11, <2% AROMATICS
<b>Supplementary precautionary statements</b>	P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide or dry powder to extinguish. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P403+P235 Store in a well-ventilated place. Keep cool.

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

<b>HYDROCARBONS, C9, AROMATICS</b>	<b>30-60%</b>
CAS number: —	EC number: 918-668-5
	REACH registration number: 01-2119455851-35-xxxx
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 3 - H226	Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.
STOT SE 3 - H335, H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	
<b>Chlorinated polymer 20</b>	<b>10-30%</b>
CAS number: 9006-03-5	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Not Classified	-

**425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING**

<b>HYDROCARBONS, C9-C11, &lt;2% AROMATICS</b>		<b>1-5%</b>
CAS number: —	EC number: 919-857-5	REACH registration number: 01-2119463258-33-XXXX
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R65. R10,R66,R67.	
<b>TOLUENE</b>		<b>&lt;1%</b>
CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01-2119471310-51-0026
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

<b>General information</b>	Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Get medical attention immediately. Do not induce vomiting.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. DO NOT use solvents or thinners
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 10 minutes. Consult a physician for specific advice.

**4.2. Most important symptoms and effects, both acute and delayed**

<b>General information</b>	Get medical attention promptly if symptoms occur after washing.
----------------------------	---

**4.3. Indication of any immediate medical attention and special treatment needed**

<b>Notes for the doctor</b>	No specific recommendations.
-----------------------------	------------------------------

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

<b>Suitable extinguishing media</b>	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.
-------------------------------------	---

**5.2. Special hazards arising from the substance or mixture**

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

**Specific hazards** Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>. Oxides of carbon. Oxides of nitrogen. Fire creates: Thermal decomposition or combustion products may include the following substances: Acid smoke or fumes. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

### 5.3. Advice for firefighters

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

### 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Vapours may accumulate on the floor and in low-lying areas. Use explosion proof electric equipment. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep container tightly closed. Keep containers upright. Protect from light. Store in closed original container at temperatures between 5°C and 25°C. Store away from the following materials: Oxidising materials. Acids. Alkalis.

**Storage class** Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### HYDROCARBONS, C9, AROMATICS

Long-term exposure limit (8-hour TWA): WEL 19 ppm 100 mg/m<sup>3</sup> vapour

##### Chlorinated polymer 20

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> total dust

##### TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m<sup>3</sup>

Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

#### HYDROCARBONS, C9, AROMATICS

<b>DNEL</b>	Consumer - Oral; Long term systemic effects: 11 mg/kg/day Consumer - Dermal; Long term systemic effects: 11 mg/kg/day Consumer - Inhalation; Long term systemic effects: 32 mg/m <sup>3</sup> Industry - Dermal; Long term systemic effects: 25 mg/kg/day Industry - Inhalation; Long term systemic effects: 150 mg/m <sup>3</sup>
<b>PNEC</b>	No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

#### Chlorinated Paraffin 48 (CAS: 63449-39-8)

<b>DNEL</b>	Industry - Inhalation; Long term systemic effects: 2.35 mg/m <sup>3</sup> Industry - Dermal; Long term systemic effects: 20 mg/kg/day Consumer - Oral; Long term systemic effects: 0.167 mg/kg/day Consumer - Dermal; Long term systemic effects: 8.3 mg/kg/day
<b>PNEC</b>	- Fresh water; 0.003 mg/l - marine water; 0.001 mg/l - STP; 60 mg/l - Sediment (Freshwater); 5710 mg/kg - Soil; 4640 mg/kg

#### HYDROCARBONS, C9-C11, <2% AROMATICS

<b>DNEL</b>	Industry - Inhalation; Long term systemic effects: 1500 mg/m <sup>3</sup> Consumer - Oral; Long term systemic effects: 300 mg/kg/day Consumer - Dermal; Long term systemic effects: 300 mg/kg/day Industry - Dermal; Long term systemic effects: 300 mg/kg/day Consumer - Inhalation; Long term systemic effects: 900 mg/m <sup>3</sup>
<b>PNEC</b>	No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

### TOLUENE (CAS: 108-88-3)

<b>DNEL</b>	Industry - Inhalation; Short term : 384 mg/m <sup>3</sup>
	Industry - Inhalation; Long term : 192 mg/m <sup>3</sup>
	Industry - Dermal; Long term : 384 mg/kg/day
	Consumer - Inhalation; Short term : 226 mg/m <sup>3</sup>
	Consumer - Inhalation; Long term : 56.5 mg/m <sup>3</sup>
	Consumer - Oral; Long term systemic effects: 8.13 mg/kg/day
	Consumer - Dermal; Long term : 226 mg/kg/day
<b>PNEC</b>	- Fresh water; 0.68 mg/l
	- Sediment; 16.39 mg/l
	- Soil; 2.89 mg/l
	- STP; 13.61 mg/l

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

#### Eye/face protection

Wear chemical splash goggles.

#### Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

#### Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Wash promptly with soap and water if skin becomes contaminated. Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

#### Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If ventilation is inadequate, suitable respiratory protection must be worn. Wear a full facepiece, supplied-air respirator.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid. Coloured liquid.
<b>Colour</b>	Various colours
<b>Odour</b>	Organic solvents.
<b>Odour threshold</b>	Not determined.
<b>pH</b>	Technically not feasible.
<b>Melting point</b>	Not determined.
<b>Initial boiling point and range</b>	Not determined.
<b>Flash point</b>	40 approx. °C Closed cup.
<b>Evaporation rate</b>	Not determined.

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

<b>Evaporation factor</b>	Not determined.
<b>Other flammability</b>	Not determined.
<b>Vapour pressure</b>	Not determined.
<b>Vapour density</b>	heavier than air
<b>Relative density</b>	1.00 - 1.10 @ @ 20 C°C
<b>Solubility(ies)</b>	Insoluble in water
<b>Partition coefficient</b>	Not determined.
<b>Auto-ignition temperature</b>	Not determined.
<b>Decomposition Temperature</b>	Not determined.
<b>Viscosity</b>	3.0 (ICI Rotothinner) P @ 25 C°C
<b>Explosive properties</b>	Not determined.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Not determined.

### 9.2. Other information

**Volatile organic compound** This product contains a maximum VOC content of 560 - 620 depending on colour g/litre.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not determined.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:  
Acids. Oxidising agents.

### 10.5. Incompatible materials

**Materials to avoid** Strong alkalis. Strong acids. Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicological effects** No data recorded.

**General information** Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

<b>Inhalation</b>	May cause respiratory system irritation. Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. The product contains organic solvents. Overexposure may depress the central nervous system, causing dizziness and intoxication.
<b>Ingestion</b>	Liquid irritates mucous membranes and may cause abdominal pain if swallowed. May cause irritation. Symptoms following overexposure may include the following: Stomach pain. Nausea, vomiting. Diarrhoea. May cause nausea, headache, dizziness and intoxication.
<b>Skin contact</b>	May be absorbed through the skin. Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema.
<b>Eye contact</b>	Irritation of eyes and mucous membranes.
<b>Route of exposure</b>	Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

### Toxicological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 3,492.0

Species Rat

Notes (oral LD<sub>50</sub>) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 3,492.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 3,160.0

Species Rabbit

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 3,160.0

##### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 6,193.0

Species Rat

Notes (inhalation LC<sub>50</sub>) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 6,193.0

##### Skin corrosion/irritation

Animal data Repeated exposure may cause skin dryness or cracking.

##### Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

##### Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.



## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### IARC carcinogenicity

None of the ingredients are listed or exempt.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H335, H336 May cause respiratory irritation. May cause drowsiness or dizziness.

**Target organs** Respiratory system, lungs Central nervous system

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

### Aspiration hazard

**Aspiration hazard** Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

### General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

### Inhalation

A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing. Vapours may cause headache, fatigue, dizziness and nausea. Central nervous system depression. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic.

### Ingestion

Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

### Skin contact

Repeated exposure may cause skin dryness or cracking. Discoloration of the skin.

### Eye contact

May cause temporary eye irritation.

### Route of exposure

Ingestion Inhalation Skin and/or eye contact

### Target organs

Central nervous system Respiratory system, lungs

### HYDROCARBONS, C9-C11, <2% AROMATICS

### Acute toxicity - oral

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,100.0

**Species** Rat

**ATE oral (mg/kg)** 5,100.0

### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 5,100.0

**Species** Rabbit

**ATE dermal (mg/kg)** 5,100.0

### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 5,100.0

**Species** Rat

**ATE inhalation (vapours mg/l)** 5,100.0

### Skin corrosion/irritation

**Skin corrosion/irritation** Not irritating.

### Serious eye damage/irritation

**Serious eye damage/irritation** Not irritating.

### Respiratory sensitisation

**Respiratory sensitisation** Not sensitising.

### Skin sensitisation

**Skin sensitisation** Not sensitising.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Chromosome aberration: Negative. This substance has no evidence of mutagenic properties.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### Reproductive toxicity

**Reproductive toxicity - fertility** Fertility: - , Inhalation, Rat This substance has no evidence of toxicity to reproduction.

**Reproductive toxicity - development** Developmental toxicity: - : , Inhalation, Rat This substance has no evidence of toxicity to reproduction.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not available.

### Aspiration hazard

**Aspiration hazard** Kinematic viscosity <= 20.5 mm<sup>2</sup>/s.

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

<b>Inhalation</b>	Vapours may cause drowsiness and dizziness. Central nervous system depression.
<b>Ingestion</b>	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
<b>Skin contact</b>	Product has a defatting effect on skin. May cause allergic contact eczema.
<b>Eye contact</b>	No specific health hazards known.
<b>Route of exposure</b>	Inhalation Dermal

### TOLUENE

#### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

#### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 5,000.0

Species Rat

ATE dermal (mg/kg) 5,000.0

#### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 20.1

Species Rat

ATE inhalation (vapours mg/l) 20.1

#### Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

### SECTION 12: Ecological information

**Ecotoxicity** There are no data on the ecotoxicity of this product. The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

#### 12.1. Toxicity

##### Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

**Toxicity** Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

#### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 9.2 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 3.2 mg/l, Daphnia magna

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

**Acute toxicity - microorganisms** EC<sub>50</sub>, 48 hours: 2.9 mg/l,

### Chronic aquatic toxicity

**Chronic toxicity - fish early life stage** NOEC, 28 days: 1.23 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Chronic toxicity - aquatic invertebrates** NOEC, 21 : 2.14 mg/l, Daphnia magna

### HYDROCARBONS, C9-C11, <2% AROMATICS

#### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, > 96 hours: 1000 mg/l, Oncorhynchus mykiss (Rainbow trout)  
Substance did not cause acute toxicity to fish

**Acute toxicity - aquatic invertebrates** Substance did not cause acute toxicity to the freshwater invertebrates  
EC<sub>50</sub>, 48 hours: >1000 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** EC<sub>50</sub>, > 72 hours: 1000 mg/l, Freshwater algae  
Substance did not cause acute toxicity to the freshwater green algae

**Acute toxicity - microorganisms** EC<sub>50</sub>, >: 100 mg/l, Activated sludge

#### Chronic aquatic toxicity

**Chronic toxicity - fish early life stage** NOEC, 28 days: 0.131 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Chronic toxicity - aquatic invertebrates** NOEC, 28 days: 0.23 mg/l, Daphnia magna

### TOLUENE

#### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 5.5 mg/l, Brachydanio rerio (Zebra Fish)

**Acute toxicity - aquatic invertebrates** LC<sub>50</sub>, 48 hours: 3.78 mg/l,

**Acute toxicity - aquatic plants** LC<sub>50</sub>, 72 hours: 10 mg/l,

### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

**Persistence and degradability** The degradability of the product is not known.

**Biodegradation** - 78%: 28 days

#### HYDROCARBONS, C9-C11, <2% AROMATICS

**Persistence and degradability** The product is readily biodegradable.

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

<b>Phototransformation</b>	Oxidises rapidly by photo-chemical reactions in air
<b>Biodegradation</b>	- 80 Degradation (%): 28 days Test - 301F Ready Biodegradability - Manometric Respiratory Test

### TOLUENE

<b>Persistence and degradability</b>	The product is biodegradable.
--------------------------------------	-------------------------------

### 12.3. Bioaccumulative potential

<b>Bioaccumulative potential</b>	No data available on bioaccumulation.
<b>Partition coefficient</b>	Not determined.

### Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

<b>Bioaccumulative potential</b>	No data available on bioaccumulation.
<b>Partition coefficient</b>	Not available.

#### HYDROCARBONS, C9-C11, <2% AROMATICS

<b>Bioaccumulative potential</b>	The product contains potentially bioaccumulating substances.
<b>Partition coefficient</b>	log Pow: 5 - 6.7

### TOLUENE

<b>Bioaccumulative potential</b>	The product is not bioaccumulating. BCF: 90,
<b>Partition coefficient</b>	: 2.65

### 12.4. Mobility in soil

<b>Mobility</b>	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
-----------------	---

### Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

<b>Mobility</b>	No data available.
-----------------	--------------------

#### HYDROCARBONS, C9-C11, <2% AROMATICS

<b>Mobility</b>	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. Readily absorbed into soil.
<b>Adsorption/desorption coefficient</b>	Not available.
<b>Surface tension</b>	24.5 mN/m @ 20°C

### TOLUENE

<b>Mobility</b>	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
-----------------	---

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

### 12.5. Results of PBT and vPvB assessment

#### Ecological information on ingredients.

##### HYDROCARBONS, C9, AROMATICS

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

##### HYDROCARBONS, C9-C11, <2% AROMATICS

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

##### TOLUENE

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

### 12.6. Other adverse effects

**Other adverse effects** The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

#### Ecological information on ingredients.

##### HYDROCARBONS, C9, AROMATICS

**Other adverse effects** None known.

##### HYDROCARBONS, C9-C11, <2% AROMATICS

**Other adverse effects** Not known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods** Avoid the spillage or runoff entering drains, sewers or watercourses.

**Waste class** When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

## SECTION 14: Transport information

**General** This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

### 14.1. UN number

**UN No. (ADR/RID)** 1263

**UN No. (IMDG)** 1263

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

UN No. (ICAO) 1263

### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** PAINT: Contains Hydrocarbons, C9, Aromatics, Class 3, PGIII, (38 C), MARINE POLLUTANT)

**Proper shipping name (IMDG)** PAINT: Contains Hydrocarbons, C9, Aromatics, Class 3, PGIII, (38 C), MARINE POLLUTANT)

**Proper shipping name (ICAO)** PAINT: Contains Hydrocarbons, C9, Aromatics, Class 3, PGIII, (38 C), MARINE POLLUTANT)

### 14.3. Transport hazard class(es)

ADR/RID class 3

IMDG class 3

ICAO class/division 3

### Transport labels



### 14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS F-E, S-E

Tunnel restriction code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### 15.2. Chemical safety assessment

## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Abbreviations and acronyms used in the safety data sheet</b>	<p>ATE: Acute Toxicity Estimate.  CAS: Chemical Abstracts Service.  DNEL: Derived No Effect Level.  GHS: Globally Harmonized System.  ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.  IMDG: International Maritime Dangerous Goods.  LD<sub>50</sub>: Lethal Dose to 50% of a test population (Median Lethal Dose).  PBT: Persistent, Bioaccumulative and Toxic substance.  PNEC: Predicted No Effect Concentration.  REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.  RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.  vPvB: Very Persistent and Very Bioaccumulative.</p>
<b>Classification abbreviations and acronyms</b>	<p>Acute Tox. = Acute toxicity  Aquatic Acute = Hazardous to the aquatic environment (acute)  Aquatic Chronic = Hazardous to the aquatic environment (chronic)  Asp. Tox. = Aspiration hazard  Carc. = Carcinogenicity  Eye Dam. = Serious eye damage  Eye Irrit. = Eye irritation  Flam. Liq. = Flammable liquid  Repr. = Reproductive toxicity  Resp. Sens. = Respiratory sensitisation  Skin Corr. = Skin corrosion  Skin Irrit. = Skin irritation  Skin Sens. = Skin sensitisation  STOT RE = Specific target organ toxicity-repeated exposure  STOT SE = Specific target organ toxicity-single exposure</p>
<b>Revision comments</b>	<p>Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Revision to sections 2, 8, 11 &amp; 12 for reclassification of solvents. Addition of EU supplier information Unique Formula Identifier (UFI) added</p>
<b>Issued by</b>	Technical Dept. (P.E.)
<b>Revision date</b>	28/01/2021
<b>Revision</b>	2.2
<b>Supersedes date</b>	04/04/2019
<b>SDS number</b>	11495
<b>SDS status</b>	Approved.



## 425/G149 - CHLORINATED RUBBER TAL, TBL & TDL BASES FOR TINTING

<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
<b>Signature</b>	Initials .....

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.