

RESICHEM 505 DAMP SEAL ACTIVATOR

Page: 1

Compilation date: 27/10/2018

Revision No: 2

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: RESICHEM DAMP SEAL SOLIDIFIER

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Company name: Resimac Limited

Unit B, Park Barn Estate

Station Road Topcliffe, Thirsk North Yorkshire

**YO7 3SE** 

United Kingdom

**Tel:** +44 (0) 1845 577498 **Email:** <u>info@resimac.co.uk</u>

# 1.4. Emergency telephone number

Emergency tel: +44 (0) 1845 577498

### **Section 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Classification under CHIP: Xn: R20/22; C: R34; Sens.: R43; Xn: R62

Classification under CLP: Acute Tox. 4: H302; Repr. 2: H361f; Skin Corr. 1B: H314; Skin Sens. 1: H317

Most important adverse effects: Harmful by inhalation and if swallowed. Causes burns. May cause sensitisation by skin

contact. Possible risk of impaired fertility.

### 2.2. Label elements

Label elements:

Hazard statements: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction. H361f: Suspected of damaging fertility.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark GHS08: Health hazard







### RESICHEM 505 DAMP SEAL ACTIVATOR

Page: 2

Precautionary statements: P102: Keep out of reach of children.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe vapours.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

P330: Rinse mouth.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P308+313: IF exposed or concerned: Get medical advice. P321: Specific treatment (see instructions on this label).

P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:

Hazard symbols: Corrosive.



Risk phrases: R20/22: Harmful by inhalation and if swallowed.

R34: Causes burns.

R43: May cause sensitisation by skin contact.

R62: Possible risk of impaired fertility.

**Safety phrases:** S1/2: Keep locked up and out of the reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show

the label where possible).

### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

### 3.2. Mixtures

# **Hazardous ingredients:**

### BENZYL ALCOHOL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
202-859-9	100-51-6	Xn: R20/22	Acute Tox. 4: H332; Acute Tox. 4: H302	30-50%

### RESICHEM 505 DAMP SEAL ACTIVATOR

Page: 3

### 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

	=/==		
90-72-2	Xn: R22; Xi: R36/38	Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%
EBIS(METHYLA	AMINE)		
1477-55-0	C: R34; Xn: R20/22; Sens.: R43	Skin Corr. 1B: H314; Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Chronic 3: H412; Acute Tox. 4: H332	1-10%
HYL-3,5,5-TRIM	ETHYLCYCLOHEXYLAMINE		
2855-13-2	Xn: R21/22; C: R34; Sens.: R43; -: R52/53	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412	1-10%
YLIDENEDIPHE	ENOL		
80-05-7	Xn: R62; Xi: R37; Xi: R41; Sens.: R43; -: R52	Repr. 2: H361f; STOT SE 3: H335; Eye Dam. 1: H318; Skin Sens. 1: H317	1-10%
PYLDIMETHYL	AMINE		
109-55-7	-: R10; Xn: R22; C: R34; Sens.: R43	Flam. Liq. 3: H226; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317	1-10%
	90-72-2  EBIS(METHYL/ 1477-55-0  HYL-3,5,5-TRIM 2855-13-2  YLIDENEDIPHE 80-05-7  PYLDIMETHYL/	EBIS(METHYLAMINE)  1477-55-0	90-72-2 Xn: R22; Xi: R36/38 Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315  EBIS(METHYLAMINE)  1477-55-0 C: R34; Xn: R20/22; Sens.: R43 Skin Corr. 1B: H314; Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Chronic 3: H412; Acute Tox. 4: H332  HYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE  2855-13-2 Xn: R21/22; C: R34; Sens.: R43; -: R52/53 Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412  YLIDENEDIPHENOL  80-05-7 Xn: R62; Xi: R37; Xi: R41; Sens.: Repr. 2: H361f; STOT SE 3: H335; Eye Dam. 1: H318; Skin Sens. 1: H317  PYLDIMETHYLAMINE  109-55-7 -: R10; Xn: R22; C: R34; Sens.: Flam. Liq. 3: H226; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1:

# Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

### RESICHEM 505 DAMP SEAL ACTIVATOR

Page: 4

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

# 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

### 7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

### RESICHEM 505 DAMP SEAL ACTIVATOR

Page: 5

### 8.1. Control parameters

### Hazardous ingredients:

### 4,4'-ISOPROPYLIDENEDIPHENOL

Workplace exposure limits:

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3	5 mg/m3	-	-

### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory

protective device with particle filter.

Hand protection: Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

# Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid Colour: Amber

**Odour:** Ammoniacal

Solubility in water: Insoluble

Viscosity: Viscous

Boiling point/range°C: >200 Flash point°C: >100

Autoflammability°C: 380 Relative density: 1.0

### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### RESICHEM 505 DAMP SEAL ACTIVATOR

Page: 6

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion

emits toxic fumes of nitrogen oxides.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

# **Hazardous ingredients:**

### **BENZYL ALCOHOL**

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

# 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

ORL	RAT	LD50	1200	mg/kg
SKN	RAT	LD50	1280	mg/kg

### M-PHENYLENEBIS(METHYLAMINE)

DERMAL	RAT	LD50	3100	mg/kg
ORAL	RAT	LD50	930	mg/kg

### 4,4'-ISOPROPYLIDENEDIPHENOL

ORL	MUS	LD50	2400	mg/kg
ORL	RAT	LD50	3250	mg/kg

### **3-AMINOPROPYLDIMETHYLAMINE**

ORL	RAT	LD50	1870	mg/kg
SKN	RBT	LD50	600	μl/kg

### RESICHEM 505 DAMP SEAL ACTIVATOR

Page: 7

### Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH ING	Hazardous: calculated
Corrosivity	OPT INH DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated
Toxicity for reproduction		Hazardous: calculated

# Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# **Section 12: Ecological information**

### 12.1. Toxicity

# Hazardous ingredients:

# M-PHENYLENEBIS(METHYLAMINE)

DAPHNIA	48H EC50	15.2	mg/l
FISH	96H LC50	>100	mg/l

# 12.2. Persistence and degradability

Persistence and degradability: Not readily biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

# 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

# Section 13: Disposal considerations

# 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

# RESICHEM 505 DAMP SEAL ACTIVATOR

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Page: 8

### RESICHEM 505 DAMP SEAL ACTIVATOR

Page: 9

### **Section 14: Transport information**

14.1. UN number

UN number: UN2735

14.2. UN proper shipping name

Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

(Isophoronediamine)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 3

# Section 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# 15.2. Chemical Safety Assessment

# **Section 16: Other information**

# Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

# RESICHEM 505 DAMP SEAL ACTIVATOR

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

Page:

### RESICHEM DAMP SEAL SOLIDIFIER

Page: 9

H335: May cause respiratory irritation.

H361f: Suspected of damaging fertility.

H412: Harmful to aquatic life with long lasting effects.

R10: Flammable.

R20/22: Harmful by inhalation and if swallowed.

R21/22: Harmful in contact with skin and if swallowed.

R22: Harmful if swallowed.

R34: Causes burns.

R36/38: Irritating to eyes and skin.
R37: Irritating to respiratory system.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

 $R52: Harmful \ to \ aquatic \ organisms.$ 

R62: Possible risk of impaired fertility.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.