



SAFETY DATA SHEET

RESICHEM 508 UVPU BASE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name UVPU ACTIVATOR COMPONENT

Product number 508

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier RESIMAC LTD,
PARK BARN ESTATE,
STATION ROAD,
TOPCLIFFE, THIRSK,
NORTH YORKSHIRE,
Y07 3SE, UNITED
KINGDOM

Tel: 01845 577498

1.4. Emergency telephone number

Emergency telephone 01845 577498 (Not 24 Hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Carc. 1B - H350 Repr. 1A - H360Df

Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Repr. Cat. 1;R61. Carc. Cat. 3;R40,Repr. Cat. 3;R62. N;R51/53. R10,R33.

Human health Harmful by inhalation and in contact with skin. The liquid may be irritating to skin. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Environmental The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical The product is flammable. Heating may generate flammable vapours.

2.2. Label elements

RESICHEM 508 UVPU BASE**Pictogram****Signal word**

Danger

Hazard statements

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H350 May cause cancer.
 H411 Toxic to aquatic life with long lasting effects.
 H360Df May damage the unborn child. Suspected of damaging fertility.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

C.I.PIGMENT YELLOW 34 (C.I. 77603), C.I.PIGMENT RED 104 (C.I. 77605)

Supplementary precautionary statements

P201 Obtain special instructions before use.
 P233 Keep container tightly closed.
 P240 Ground/ bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P264 Wash contaminated skin thoroughly after handling.
 P273 Avoid release to the environment.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P308+P313 IF exposed or concerned: Get medical advice/ attention.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P391 Collect spillage.
 P405 Store locked up.

2.3. Other hazards**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

BUTYL ACETATE -norm	10-30%
CAS number: 123-86-4	EC number: 204-658-1
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226	R10 R66 R67
STOT SE 3 - H336	

RESICHEM 508 UVPU BASE

XYLENE		10-30%
CAS number: 1330-20-7		EC number: 215-535-7
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xn;R20/21 Xi;R38	
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
Asp. Tox. 1 - H304		
C.I.PIGMENT YELLOW 34 (C.I. 77603)		5-10%
CAS number: 1344-37-2		EC number: 215-693-7
M factor (Acute) = 1		M factor (Chronic) = 1
Classification	Classification (67/548/EEC or 1999/45/EC)	
Carc. 1B - H350	Carc. Cat. 3;R40 Repr. Cat. 1;R61 Repr. Cat. 3;R62 R33	
Repr. 1A - H360Df	N;R50/53	
STOT RE 2 - H373		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		
C.I.PIGMENT RED 104 (C.I. 77605)		1-5%
CAS number: 12656-85-8		EC number: 235-759-9
M factor (Acute) = 1		M factor (Chronic) = 1
Classification	Classification (67/548/EEC or 1999/45/EC)	
Carc. 1B - H350	Carc. Cat. 3;R40 Repr. Cat. 1;R61 Repr. Cat. 3;R62 R33	
Repr. 1A - H360Df	N;R50/53	
STOT RE 2 - H373		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		
2-METHOXY-1-METHYLETHYL ACETATE		1-5%
CAS number: 108-65-6		EC number: 203-603-9
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xi;R36	
ETHYLBENZENE		1-5%
CAS number: 100-41-4		EC number: 202-849-4
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Xn;R20	
Acute Tox. 4 - H332		
Asp. Tox. 1 - H304		

RESICHEM 508 UVPU BASE

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY		<1%
CAS number: 64742-48-9		EC number: 265-150-3
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	Xn;R65. R10,R66.	
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
BUTANOL-norm		<1%
CAS number: 71-36-3		EC number: 200-751-6
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xn;R22 Xi;R37/38,R41 R67	
Acute Tox. 4 - H302		
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
STOT SE 3 - H335, H336		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures**4.1. Description of first aid measures**

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
Inhalation	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Skin contact	Immediately remove contaminated clothing. Rinse immediately with plenty of water. Remove contaminated clothing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed**4.3. Indication of any immediate medical attention and special treatment needed****SECTION 5: Firefighting measures****5.1. Extinguishing media**

Suitable extinguishing media Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

RESICHEM 508 UVPU BASE

5.3. Advice for firefighters

Protective actions during firefighting	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.
--------------------------------	---

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.
--------------------------	---

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container. Avoid contact with oxidising agents.
----------------------------	--

Storage class	Flammable liquid storage.
----------------------	---------------------------

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m³(Sk)

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m³(Sk)

RESICHEM 508 UVPU BASE

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m³

BUTANOL-norm

Long-term exposure limit (8-hour TWA): WEL

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 154 mg/m³(Sk)

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Rubber (natural, latex).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

Wear a respirator fitted with the following cartridge: Organic vapour filter.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Various colours.
Odour	Characteristic.
Flash point	23 - 55°C
Vapour density	Heavier than air
Relative density	1.30 - 1.50

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of 440 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

RESICHEM 508 UVPU BASE

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg) 10,207.02

Acute toxicity - inhalation

ATE inhalation (gases ppm) 37,580.4

ATE inhalation (vapours mg/l) 91.86

ATE inhalation (dusts/mists mg/l) 12.53

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Harmful by inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Ingestion Gastrointestinal symptoms, including upset stomach. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin contact Product has a defatting effect on skin. May cause allergic contact eczema. Irritating to skin. Harmful in contact with skin.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

SECTION 12: Ecological Information

Ecotoxicity The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

RESICHEM 508 UVPU BASE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III

RESICHEM 508 UVPU BASE

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code •3YE

Hazard Identification Number 33
(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EH40/2005 Workplace exposure limits.

Guidance Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date 29/01/2016

Revision 5

Supersedes date 11/11/2015

SDS number 31850

Risk phrases in full

R10 Flammable.

R11 Highly flammable.

R20 Harmful by inhalation.

R20/21 Harmful by inhalation and in contact with skin.

R33 Danger of cumulative effects.

R36 Irritating to eyes.

R38 Irritating to skin.

R40 Limited evidence of a carcinogenic effect.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R61 May cause harm to the unborn child.

R62 Possible risk of impaired fertility.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

RESICHEM 508 UVPU BASE

Hazard statements in full	H225 Highly flammable liquid and vapour.
	H226 Flammable liquid and vapour.
	H302 Harmful if swallowed.
	H304 May be fatal if swallowed and enters airways.
	H312 Harmful in contact with skin.
	H315 Causes skin irritation.
	H318 Causes serious eye damage.
	H332 Harmful if inhaled.
	H335 May cause respiratory irritation.
	H336 May cause drowsiness or dizziness.
	H350 May cause cancer.
	H360Df May damage the unborn child. Suspected of damaging fertility.
	H373 May cause damage to organs through prolonged or repeated exposure.
	H400 Very toxic to aquatic life.
	H410 Very toxic to aquatic life with long lasting effects.
	H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.