

Asphalt & Concrete Resurfacer

Seals, resurfaces and transforms worn and drab asphalt & concrete



Watco Asphalt & Concrete Resurfacer is a thick water based acrylic paint style coating that seals and resurfaces damaged and worn surfaces. Easily applied by roller. It forms a flexible, sealed, waterproof surface that transforms old asphalt, concrete and tarmac. It provides a tough flexible surface for cars and pedestrians.



Areas of use:

- Car parks
- Driveways
- Playgrounds

Features:

- Ready mixed and easily roller applied
- Non-hazardous and low odour acrylic formula
- Excellent adhesion and covering power
- Quick drying (24 hours for light traffic)
- Excellent resistance to UV and weathering
- Can be applied up to a maximum depth of 1mm in one application. Multiple coats can be applied for badly worn patches
- Suitable for pedestrian and light-medium traffic (cars, not HGV's or forklifts)
- *Not suitable for mastic asphalt

Colours



Samples are available on request. While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Asphalt & Concrete Resurfacer**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



Asphalt & Concrete Resurfacer

Seals, resurfaces and transforms worn and drab asphalt & concrete

1 Surface Preparation

Ensure surfaces are clean, dry and free of loose material. If the surface has been previously painted, remove as much paint as possible by mechanical means. Any remaining paint should be well bonded and lightly abraded to provide a key. Watco Bio-D, a bio-degradable water based degreasant can be used for grease removal from concrete and asphalt.

2 Mixing

Stir the contents well with a wide bladed mixing tool to ensure that the product has not settled in transit.

3 Application

Apply only in dry conditions (above 10°C and below 35°C). Do not apply in cold, damp conditions or when rain is forecast. In warmer conditions 25°C - 35°C dry, hot surfaces should be slightly dampened first. Pour onto the surface in ribbons and spread it out with a medium pile roller. Apply thinly. The second coat can be applied as soon as the first coat has dried. Further thin multiple coats can be applied for badly worn areas.

Important – Do not apply the product in layers thicker than 1 mm. Never add water to the product.

4 Safety

All product labels provide general safety information. Material Safety Data Sheets are available.

5 Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

Asphalt & Concrete Resurfacer

Seals, resurfaces and transforms worn and drab asphalt & concrete

Specification

Composition	Water based acrylic coating.
Number of Components	1
Finish	Matt, slip resistant surface.
Primer Required	No.
Number of Coats	1 usually sufficient.
Usage Interior/Exterior	Exterior.
Application Tools	Medium pile roller.
Suitable For	Concrete or Asphalt & Tarmac, over 3 months old
Pack Size	25kg
Coverage	25kg will cover approximately 15m ² at 1mm thick. Coverage can depend upon the texture of the substrate.
Curing Time	Protect from rain for 6 to 12 hours following application. Touch dry/Light traffic: 24 hours at 10°C - 15°C, 15 - 20 hours at 15°C - 30°C Heavy traffic: 2 - 3 days at 10°C - 15°C, 2 days at 15°C - 30°C.
Cleaning Tools	Wash in warm, soapy water before the product dries, otherwise soak for 24 hours in White Spirit.
Storage	Store between 5°C and 25°C out of direct sunlight.
Shelf Life	24 months in unopened container.
Safety	Material Safety Data Sheets are available. All foods should be removed during application and curing.

Principle Limitations Please contact us regarding applications not described here.	Do not apply Watco Asphalt & Concrete Resurfacer too thickly in one application. This can cause a delay in the drying process and may lead to cracking. Watco Asphalt Resurfacer produces a tough, flexible layer. However, if applied over a crack (when the crack has been caused by movement) it may crack if significant movement re-occurs. The product is sufficiently flexible to tolerate the usual expansion and contraction associated with asphalt. The product will seal the substrate and as such could add to puddling on poorly drained areas during wet weather. Apply only in dry, warm (above 10°C) conditions when rain is not forecast.
--	---