

Page 1/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 9 (replaces version 8)

Revision: 13.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name Epoxy BS 2000 Komp. A

Article number: 6001-6010

1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. **Application of the substance / the mixture** Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Remmers GmbH Bernhard-Remmers-Str. 13 D-49624 Löningen / Germany Mano Tel.: +49(0)5432/83-0 Fax: +49(0)5432/3985 Information department: Product Safety department: Phone: +44 (0) 1293 594 010 Email: sales@remmers.co.ukk

Remmers (UK) Limited Unit 4 , Lloyds Court Manor Royal, Crawley – West Sussex RH10 9QU fon +44 (0) 1293 594 010 fax +44 (0) 1293 594 037

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number: within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Eye Dam. 1 H318 Causes serious eye damage.

STOT RE 2 H373 May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. Hazard pictograms



Signal word Danger

Hazard-determining components of labelling:

Linseed oil polymer with bisphenol A, bisphenol A diglycidyl ether, diethylenetriamine, formaldehyde, glycidyl Ph ether and pentaethylenehexamine quartz flour

Hazard statements

H318 Causes serious eye damage.

Page 2/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 9 (replaces version 8)

Revision: 13.12.2022

Trade name Epoxy BS 2000 Komp. A

(Contd. of page 1) H373 May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements

| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. | |
|---|---|--|
| P280 | Wear protective gloves / eye protection / face protection. | |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact | |
| | lenses, if present and easy to do. Continue rinsing. | |
| P310 | Immediately call a POISON CENTER/doctor. | |
| P314 | Get medical advice/attention if you feel unwell. | |
| P501 | Dispose of contents/container in accordance with local/regional/national/ | |
| | international regulations. | |
| Additional information: | | |
| EUH208 Contains 2.2'-iminodiethylamine, 3.6.9-triazaundecamethylenediamine, 3.6.9.12-tetra- | | |

EUH208 Contains 2,2'-iminodiethylamine, 3,6,9-triazaundecamethylenediamine, 3,6,9,12-tetra azatetradecamethylenediamine. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

| Dangerous components [% w/w]: | | | | |
|--|--|-------------|--|--|
| CAS: 7727-43-7 EINECS: 231-784-4 | barium sulphate, natural substance with a Community workplace exposure limit | ≥10-<20% | | |
| CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17- XXXX | titanium dioxide Carc. 2, H351 | ≥10-<20% | | |
| CAS: 68915-81-1 | Linseed oil polymer with bisphenol A, bisphenol A diglycidyl ether, diethylenetriamine, formaldehyde, glycidyl Ph ether and pentaethylenehexamine Eye Dam. 1, H318; Skin Irrit. 2, H315 | ≥5-<10% | | |
| CAS: 14808-60-7 EINECS: 238-878-4 Reg.nr.: 01-2120770509-45- XXXX | quartz flour STOT RE 1, H372 | ≥1-<2.5% | | |
| CAS: 111-40-0 EINECS: 203-865-4 Index number: 612-058-00-X Reg.nr.: 01-2119473793-27- XXXX | 2,2'-iminodiethylamine Acute Tox. 2, H330; Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; STOT SE 3, H335 | ≥0.1-≤0.25% | | |
| CAS: 112-57-2 EINECS: 203-986-2 Index number: 612-060-00-0 | 3,6,9-triazaundecamethylenediamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317 | ≥0.1-<0.25% | | |
| CAS: 4067-16-7 EINECS: 223-775-9 Index number: 612-064-00-2 Reg.nr.: 01-2119485826-22- XXXX | 3,6,9,12-tetra-azatetradecamethylenediamine Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317 | ≥0.1-<0.25% | | |

Additional information For the wording of the listed hazard phrases refer to section 16.

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 9 (replaces version 8)

Printing date 13.12.2022

Revision: 13.12.2022

Trade name Epoxy BS 2000 Komp. A

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information When symptoms occur or in case of doubt, seek medical advice **After inhalation** Take affected persons into the open air and position comfortably **After skin contact** If skin irritation continues, consult a doctor. **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor. **After swallowing** Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment. 5.2 Special hazards arising from the substance or mixture May be released in case of fire Nitrogen oxides (NOx) Formation of poisonous gases during heating or in fires. 5.3 Advice for firefighters Protective equipment: Wear self-contained breathing apparatus. Wear full protective suit. Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Dilute with plenty of water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation. **6.4 Reference to other sections** See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas. Ensure good ventilation/exhaust in workplaces. Avoid the formation of aerosols. Information about protection against explosions and fires: Keep breathing equipment ready.

7.2 Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and containers: No special requirements.
Information on storage in a common storage facility: none
Further information about storage conditions:
Store container in a well ventilated position.
Protect from frost.
Keep container tightly closed.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 9 (replaces version 8)

Revision: 13.12.2022

Trade name Epoxy BS 2000 Komp. A

(Contd. of page 3)

| SECTION 8: Exposure controls/personal protection | | |
|--|--|--|
| 8.1 Control parameters | | |
| Components with limit values that require monitoring at the workplace: | | |
| CAS: 7727-43-7 barium sulphate, natural | | |
| WEL Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust | | |
| CAS: 13463-67-7 titanium dioxide | | |
| WEL Long-term value: 10* 4** mg/m ³ *total inhalable **respirable | | |
| CAS: 111-40-0 2,2'-iminodiethylamine | | |
| WEL Long-term value: 4.3 mg/m³, 1 ppm Sk | | |
| Additional information: The lists that were valid during compilation were used as a basis. | | |

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Store protective clothing separately.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

Respiratory equipment:

Not necessary if room is well-ventilated.

Only use ambient air independent respiratory equipment in pits, shafts and silos!

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 9 (replaces version 8)

Revision: 13.12.2022

Trade name Epoxy BS 2000 Komp. A

(Contd. of page 4)

| SECTION 9: Physical and chemical proper | ties |
|--|---|
| 9.1 Information on basic physical and chemical | properties |
| General Information | |
| Physical state | Fluid |
| Colour: | According to product specification |
| Odour: | Amine-like |
| Odour threshold: | Not determined. |
| Melting point/freezing point: | Not determined |
| Boiling point or initial boiling point and boiling | |
| range | Not determined |
| Flammability | Not applicable. |
| Lower and upper explosion limit | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| Flash point: | >105 °C |
| Ignition temperature: | not applicable |
| Decomposition temperature: | Not determined. |
| pH | Not determined. |
| Viscosity: | Not dotominiou. |
| Kinematic viscosity | Not determined. |
| dynamic at 20 °C: | 1,900 mPas |
| Solubility | |
| Water: | Fully miscible |
| Partition coefficient n-octanol/water (log value) | |
| Vapour pressure at 20 °C: | 23 hPa |
| Density and/or relative density | 2511Fa |
| | $1.45 \mathrm{a/om^3}$ |
| Density at 20 °C: | 1.45 g/cm ³ Not determined. |
| Relative density | |
| Vapour density | Not determined. |
| 9.2 Other information | |
| Appearance: | |
| Form: | Fluid |
| Important information on protection of health | |
| and environment, and on safety. | |
| Explosive properties: | Product is not explosive. |
| Solvent separation test | < 3 % |
| Change in condition | |
| Evaporation rate | Not determined. |
| Information with regard to physical hazard | |
| classes | |
| Explosives | Void |
| Flammable gases | Void |
| Aerosols | Void |
| Oxidising gases | Void |
| Gases under pressure | Void |
| Flammable liquids | Void |
| Flammable solids | Void |
| Self-reactive substances and mixtures | Void |
| Pyrophoric liquids | Void |
| Pyrophoric solids | Void |
| Self-heating substances and mixtures | Void |
| Substances and mixtures, which emit | |
| flammable gases in contact with water | Void |
| Oxidising liquids | Void |
| Oxidising solids | Void |
| Organic peroxides | Void |
| Corrosive to metals | Void |
| | VOID |

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 9 (replaces version 8)

Revision: 13.12.2022

Trade name Epoxy BS 2000 Komp. A

(Contd. of page 5)

Desensitised explosives

Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions Exothermic reaction with acids

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: Acids

10.6 Hazardous decomposition products: Nitrous vitriol gases

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

CAS: 111-40-0 2,2'-iminodiethylamine

Oral LD50 1,080 mg/kg (rat)

Dermal LD50 1,090 mg/kg (rabbit)

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Causes serious eye damage.

Sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure:

May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation. **Aspiration hazard:** Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes: Do not allow product to reach ground water, bodies of water or sewage system.

SECTION 13: Disposal considerations

Recommendation

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Page 7/8

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 9 (replaces version 8)

Printing date 13.12.2022

Revision: 13.12.2022

Trade name Epoxy BS 2000 Komp. A

(Contd. of page 6)

Uncleaned packaging: Recommendation:

Disposal must be made according to official regulations. Packaging can be reused or recycled after cleaning. **Recommended cleaning agent:** Water, if necessary with cleaning agent.

SECTION 14: Transport information

| 14.1 UN number or ID number ADR, ADN, IMDG, IATA | Void | |
|--|--|--|
| 14.2 UN proper shipping name ADR, ADN, IMDG, IATA | Void | |
| 14.3 Transport hazard class(es) | | |
| ADR, ADN, IMDG, IATA Class | Void | |
| 14.4 Packing group ADR, IMDG, IATA | Void | |
| 14.5 Environmental hazards: Marine pollutant: | No | |
| 14.6 Special precautions for user | Not applicable. | |
| 14.7 Maritime transport in bulk according to IMO instruments Not applicable. | | |
| Transport/Additional information: | Not a hazardous good according to the above regulations. | |
| UN "Model Regulation": | Void | |
| | | |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Page 8/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 9 (replaces version 8)

Revision: 13.12.2022

(Contd. of page 7)

Trade name Epoxy BS 2000 Komp. A

H411 Toxic to aquatic life with long lasting effects. Classification according to Regulation (EC) No 1272/2008 Calculation method Department issuing data specification sheet: Product Safety department / EHS Date of previous version: 09.04.2020 Version number of previous version: 8 Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity – Category 2 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2