

Bitu-Mend® Advanced

For the strongest ever asphalt repairs



Watco Bitu-Mend® Advanced is ideal for filling holes in asphalt and similar type floors. The epoxy resin formulation is much stronger and longer lasting than traditional bitumen based products. It's strength allows for thinner repairs than conventional products and it is ideal for heavily trafficked areas. It has good general resistance to many chemicals commonly found in Industry. Please contact us for advice regarding other chemicals.



Areas of use:

- Potholes in asphalt and tarmac
- Gangways and work areas
- Car parks and loading bays where forklifts and lorries operate
- Splits and cracks in asphalt
- Roller shutter door guide rails

Features:

- Cures to a hard, black, slip resistant finish
- Can be applied at any thickness from 10mm - 100mm
- Can also be used on concrete
- Ready for use in 12 hours

Colours



Black

Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Bitu-Mend® Advanced**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



Bitu-Mend[®] Advanced

For the strongest ever asphalt repairs

1 Surface Preparation

Ensure the void to be filled is clean, dry (slight damp is acceptable) and sound. Prime surfaces with Watco Tack Coat

2 Mixing

Mixing is easier on a board, but it can be done in the plastic container provided. Empty the contents of the smaller curing agent tin into the larger resin tin and mix thoroughly using a palette knife or similar wide bladed tool. Immediately empty the mixed components onto the granite aggregate. Mix using a trowel to achieve a loose textured black compound. Ensure that the dry aggregate is thoroughly coated.

3 Application

Tip the mixed product into the void and work into any gaps and crevices with a trowel. Lightly tamp down with a piece of wood, compacting the product to remove air pockets. Finish with a trowel.

4 Safety

Material Safety Data Sheets are available.

5 Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

Bitu-Mend[®] Advanced

For the strongest ever asphalt repairs

Specification

Composition	A blend of graded granite aggregate and epoxy resin.
Number of Components	1 x resin, 1 x curing agent, 1 x aggregate.
Finish	Granular, black, slip resistant surface.
Primer Required	Watco Tack Coat.
Usage Interior/Exterior	Interior & exterior.
Application Tools	Trowel.
Suitable For	Concrete, sand & cement, asphalt, tarmac.
Pack Size	25kg
Coverage	1m ² at 15mm thick.
Pot Life	Working life of mixed components: Approximately 30 minutes at 10°C.
Curing Time	Can be walked on after 8-12 hours and subject to heavy traffic after 12-24 hours (all at 10°C - 20°C). Lower temperatures will extend the curing time.
Shelf Life	12 months in unopened containers.
Storage	Store above 10°C.
Safety.	All product labels provide general safety information. Material Safety Data Sheets are available. Food products must be removed from the area during application and cure.