



[LANG_VERFUEGBARKEIT]			
[LANG_ANZ_PAL]			
[LANG_VERPACKUNGSEINHEITEN]	12,5 [LANG_SIZE_UNIT_KILOGRAM]	25 [LANG_SIZE_UNIT_KILOGRAM]	
[LANG_GEBINDE_TYP]	[set_im_karton]	[set_im_karton]	
[LANG_GEBINDE_SCHLUESSEL]	13	25	
[LANG_ART_NR]			
6860	■	■	

[LANG\_ANWENDUNGSBEREICHE] ■ [AW\_GR\_230]

[LANG\_EIGENSCHAFTEN] ■ [EG\_GR\_197]  
■ [EG\_M\_116]  
■ [EG\_GR\_25]

[LANG\_ARBEITSVORBEREITUNG] ■ [LANG\_ANFORDERUNGEN\_UNTERGRUND]  
[U1\_B\_104]  
[U1\_B\_1]  
[U1\_B\_2]  
[U1\_B\_15]  
[U1\_B\_16]  
  
■ [LANG\_VORBEREITUNGEN]  
[U2\_B\_1]  
[U2\_B\_21]  
[U2\_B\_22]

[LANG\_ZUBEREITUNG] ■ [LANG\_ANMISCHUNG]  
[ZBK\_B\_101]  
[ZBK\_B\_94]  
[ZBK\_B\_35]  
[ZBK\_B\_96]  
[ZBK\_B\_40]  
  
[ZBK\_B\_53]

A:B:C:D	
A: 2,5	3 Min.
B: 2,6	
C: 7,0	
D: 0,4	

[LANG\_VERARBEITUNG] [LANG\_NUR\_GEWERBLICH]

■ [LANG\_VERARBEITUNGSBEDINGUNGEN]  
[VA\_VT\_10\_20\_o]  
[VA\_B\_21]  
[VA\_B\_7]  
[VA\_B\_8]  
  
■ [LANG\_UEBERBESCHICHTBARKEIT\_20]  
[H\_D\_27]  
[VA\_B\_77]  
  
[VA\_B\_1]

≤ +20 °C	POTLIFE
≥ +10 °C	5 Min.

[LANG\_ANWENDUNGSBEISPIELE] ■ [anwendungsbeispiele\_2]  
[AB\_B\_134]

[LANG\_HINWEISE] [H\_B\_129]



[H\_B\_25]  
[H\_B\_104]  
[H\_B\_106]  
[H\_B\_186]  
[H\_B\_26]  
[leer\_zeile\_bausteine]  
[H\_B\_7]


[LANG\_ARBEITSGERAETE\_REINIGUNG]

[GR\_B\_2]  
[GR\_B\_3]  
[GR\_B\_4]



[LANG\_LAGERUNG\_HALTBARKEIT]

[LG\_A\_43]



[LANG\_ENTSORGUNGSHINWEIS]

[SR\_E\_1]

[LANG\_LEISTUNGSERKLAERUNG]

➤ [Leistungserklärung](#)

[LANG\_TM\_DISCLAIMER\_1]

[LANG\_TM\_DISCLAIMER\_2]

[LANG\_TM\_DISCLAIMER\_3]