

TECHNICAL DATASHEET

3 IN 1 ADMIXTURE

Description & Uses

3 in 1 Admixture from Alpha Chem is an air entraining chloride free liquid admixture for waterproofing, plasticising and retarding of render mixes. Conforms to BS4887 air entraining properties.

AlphaChem 3 in 1 Admixture has the benefits of being an air-entrainer and retarder, allowing for large areas to be covered in one single application hence improving workability, trowel-ability and significantly reducing water penetration. The improved durability reduces efflorescence and shrinkage.

Directions

- Ensure all surfaces are clean, sound, dry and free from dust, loose materials, grease or other contaminants.
- Work must be carried out in accordance with code of practice BS5262(1991) or external renders.
- Add to mix at an addition rate of 500 – 1000ml per 50kg of cement, dependant on the degrees of plasticising / retardation required.
- Alternatively add to mixing drum of 1 part 3 in 1 Admixture to 20/40 parts water. Please remember to reduce the required water amount up to 20%

Storage

Store in cool, dry conditions between +5°C and +30°C. Protect from frost.

Shelf Life

24 months when stored in original, unopened packaging.

Limitations

- Ensure not to over mix.
- Is not a replacement for DPC.
- It is the user's responsibility to ensure suitability for use. Safety Data available on request.
- Read the label carefully for essential health and safety information prior to use.

Technical Data

Chloride Ion Content	<0.1% by w/w (nil)

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.