

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.12.2022 Version number 5 (replaces version 4) Revision: 13.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name EPOXY FAS 100 KOMP. A

Article number: 0916

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Remmers (UK) Limited Bernhard-Remmers-Str. 13

Unit 4, Lloyds Court

D-49624 Löningen / Germany Manor Royal, Crawley - West Sussex RH10 9QU Tel.: +49(0)5432/83-0

fon +44 (0) 1293 594 010 fax +44 (0) 1293 594 037

Fax: +49(0)5432/3985 Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

H315 Causes skin irritation. Skin Irrit. 2

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS07 GHS09

Signal word Warning

Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) [[(2-ethylhexyl)oxy]methyl]oxirane

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.12.2022 Version number 5 (replaces version 4) Revision: 13.12.2022

Trade name EPOXY FAS 100 KOMP. A

(Contd. of page 1)

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

| Dangerous components [% w/w]: | | |
|--------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26- XXXX | reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % | ≥70-≤85% |
| CAS: 28064-14-4 NLP: 500-006-8 Reg.nr.: 01-2119454392-40- XXXX | bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317 | ≥10-<20% |
| CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38- XXXX | benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332 | ≥5-<10% |
| CAS: 2461-15-6 EINECS: 219-553-6 Reg.nr.: 01-2119962196-31- XXXX | [[(2-ethylhexyl)oxy]methyl]oxirane Skin Irrit. 2, H315; Skin Sens. 1, H317 | ≥1-<2.5% |

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation

Use a respiration bag or breathing device.

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact Wash immediately with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 5 (replaces version 4)

Trade name EPOXY FAS 100 KOMP. A

(Contd. of page 2)

Revision: 13.12.2022

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Water spray jet

Carbon dioxide

Foam

Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen chloride (HCI)

further harmful conflagration gases and fumes

5.3 Advice for firefighters

Protective equipment: Wear self-contained breathing apparatus.

Additional information

Cool endangered containers with water spray iet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

Information about protection against explosions and fires: No special requirements.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and containers: Prevent any penetration into the ground.

Information on storage in a common storage facility:

Store away from oxidising agents.

Store away from food.

Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.12.2022 Version number 5 (replaces version 4) Revision: 13.12.2022

Trade name EPOXY FAS 100 KOMP. A

Individual protection measures, such as personal protective equipment General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euigment is not required or the amount of the PPE can be adpated accordingly.

Respiratory equipment:

In case of a risk of inhaling, wear half-mask with combination filter for organic vapours and particles. Filter A/P2.

Only use ambient air independent respiratory equipment in pits, shafts and silos!

Hand protection

Long cuffed gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid Colour: Clear

Weak, characteristic Odour: **Odour threshold:** Not determined. Melting point/freezing point: Not determined

Boiling point or initial boiling point and boiling

>100 °C range **Flammability** Not applicable.

Lower and upper explosion limit

Lower: Not determined. Upper: Not determined. >100 °C Flash point: Ignition temperature: not applicable **Decomposition temperature:** Not determined. pН Not determined.

Viscosity:

Kinematic viscosity Not determined. dynamic at 20 °C: 900-950 mPas

(Contd. on page 5)

(Contd. of page 3)

according to 1907/2006/EC, Article 31

Version number 5 (replaces version 4) Printing date 13.12.2022 Revision: 13.12.2022

Trade name EPOXY FAS 100 KOMP. A

(Contd. of page 4)

Solubility

Water: Not miscible or difficult to mix

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 1.15-1.16 g/cm³ Relative density Not determined. Vapour density Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health

and environment, and on safety.

Explosive properties: Product is not explosive.

Solvent separation test < 3 %

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard

classes **Explosives** Void Flammable gases Void Void **Aerosols** Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void Oxidising solids Void Organic peroxides Void **Corrosive to metals** Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Desensitised explosives

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions Exothermic polymerisation

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

May be released in fire:

Carbon monoxide and carbon dioxide

Hydrogen chloride (HCI)

Phenol

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Void

Acute toxicity: Based on available data, the classification criteria are not met.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 5 (replaces version 4)

Trade name EPOXY FAS 100 KOMP. A

(Contd. of page 5)

Revision: 13.12.2022

LD/LC50 values that are relevant for classification: CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

LD50 >10,000 mg/kg (rat) Dermal LD50 >2,000 mg/kg (rat)

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met. STOT-single exposure: Based on available data, the classification criteria are not met. STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Toxic for fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN3082

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 5 (replaces version 4)

Trade name EPOXY FAS 100 KOMP. A

(Contd. of page 6)

Revision: 13.12.2022

| 14.2 UN proper shipping name | | |
|----------------------------------------------|---------------------------------------------------------------------------------------------|--|
| ADR | 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction | |
| | product: bisphenol A-(epichlorhydrin) (number average | |
| IMDG | molecular weight ≤ 700))) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, | |
| | LIQUID, N.O.S. (Epoxy Resin (reaction product: | |
| | bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700))), MARINE POLLUTANT | |
| IATA | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, | |
| | LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average | |
| | molecular weight ≤ 700))) ´ ` | |
| 14.3 Transport hazard class(es) | | |
| ADR | | |
| | | |
| Class | 9 (M6) Miscellaneous hazardous substances and articles. | |
| Label | 9 | |
| IMDG | | |
| 1 1 1 1 1 1 1 1 1 1 | | |
| Class Label | 9 Miscellaneous hazardous substances and articles. 9 | |
| IATA | | |
| | | |
| Class Label | 9 Miscellaneous hazardous substances and articles.9 | |
| 14.4 Packing group ADR, IMDG, IATA | III | |
| 14.5 Environmental hazards: | | |
| Marine pollutant: | Yes Symbol (fish and tree) | |
| Special marking (ADR): | Symbol (fish and tree) | |
| 14.6 Special precautions for user | Warning: Miscellaneous hazardous substances and articles. | |
| hazard identification number: | 90 | |
| EMS Number: Stowage Category | F-A,S-F A | |
| 14.7 Maritime transport in bulk according to | | |
| IMO instruments Not applicable. | | |
| <u> </u> | | |

(Contd. on page 8)

according to 1907/2006/EC, Article 31

Version number 5 (replaces version 4) Printing date 13.12.2022

Trade name EPOXY FAS 100 KOMP. A

(Contd. of page 7)

Revision: 13.12.2022

| Transport/Additional information: | | |
|--------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| ADR | | |
| Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml | |
| Transport category Tunnel restriction code | 3 (-) | |
| IMDG | | |
| Limited quantities (LQ) | 5L | |
| Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml | |
| UN "Model Regulation": | UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (REACTION PRODUCT: BISPHENOL A- (EPICHLORHYDRIN) (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700))), 9, III | |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

Harmful if swallowed. H302

Causes skin irritation. H315

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

Toxic to aquatic life with long lasting effects. H411

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Date of previous version: 12.05.2020

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 5 (replaces version 4)

Trade name EPOXY FAS 100 KOMP. A

(Contd. of page 8)

Revision: 13.12.2022

Version number of previous version: 4 Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2