

Flexible Crack Sealant (Tremco SP540)

An easy to use, cartridge based flexible crack filler

Watco Flexible Crack Sealant fills and seals joints or cracks approximately 3mm - 25mm wide in concrete floors. It can be over-painted after 24 hours, but any future movement of the substrate could cause a hairline crack to appear in the paint. Our most appropriate coating for floors liable to slight movement is Watco Flexicoat.



Areas of use:

- Cracks in concrete or asphalt floors
- Perimeter seals
- Trafficable floor joints

Features:

- Easy to apply with standard skeleton gun
- Flexible, moves with substrate (+/- 25%)
- Hardwearing - suitable for areas subject to heavy traffic
- Excellent adhesion with no primer needed
- 'concrete grey' colour - blends in with existing concrete surfaces
- Rapid cure - tack free in under 4 hours
- Can be overpainted



Colours



Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Flexible Crack Sealant**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



Flexible Crack Sealant (Tremco SP540)

An easy to use, cartridge based flexible crack filler

1 Surface Preparation

Joints and cracks should be clean, dry, sound and free from grease and any other substances likely to impair adhesion.

2 Application

Temperature should be between 5°C and 40°C.

1. Unscrew the nozzle and cut the top off the cartridge.
2. Cut the cartridge nozzle to the desired size to match the width of the joint or crack.
3. Place in a conventional skeleton gun and apply. Within 10 minutes of application press sealant down with an appropriate tool to ensure full firm contact.

3 Safety

Material Safety Data Sheets are available. Wash hands immediately after use and before eating. Wear suitable protective gloves.

4 Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale. The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

Flexible Crack Sealant (Tremco SP540)

An easy to use, cartridge based flexible crack filler

Specification

Composition	One part moisture curing polyurethane sealant.
Number of Components	1
Usage Interior/ Exterior	Exterior & interior.
Application Tools	Skeleton Gun.
Suitable For	Concrete, asphalt, tarmac, metal, stone, brick, enamel, wood, GRP and plastics.
Pack Size	310ml
Coverage	See chart labelled 'Coverage rates' below.
Overpainting	After approximately 24 hours dependant on temperature and humidity.
Cleaning	Excess sealant can easily be removed with a damp cloth. Fully cured sealant can only be removed by abrasion.
Shelf Life	12 months in unopened container.
Curing	Tack free in less than 4 hours. 3mm will fully cure after 24 hours, 6mm after 48 hours, at 20°C.
Storage	Do not allow to freeze.
Safety	All product labels provide general safety information. Material Safety Data Sheets are available. Wash hands immediately after use and before eating. Wear suitable protective gloves.

Coverage rates

Linear metres per 310ml cartridge.

Width (mm)	6	10	15	20	25
6mm deep	8.6	5.2	-	-	-
10mm deep	-	3.1	2.0	1.5	-
12mm deep	-	-	-	-	1.0