

## SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/8

# Reprotec Floor Doctor Rapid - Curing Agent

Revision 0 Revision date 2018-10-16

SECTION 1: Identification of the substance/mixture and of the company/undertaking					
1.1. Product identifier	1.1. Product identifier				
Product name	Reprotec Floor Doctor Rapid - Curing Agent				
1.2. Relevant identified uses of t	he substance or mixture and uses advised against				
Product Use [SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing; [ERC2] Formulation of preparations;					
1.3. Details of the supplier of the	1.3. Details of the supplier of the safety data sheet				
Company	RMS (Repair & Maintenance Suppliers) Ltd				
Address	2 Lighthouse View Spectrum Business Park Seaham SR7 7PR				
Web	www.rmsuppliers.com				
Telephone	0191 3897067				
Email address of the	sales@rmsuppliers.com				

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

2.1.1. Classification -	C; R34 Xn; R20/21/22 Xi; R43 R52/53		
1999/45/EC	Symbols: C: Corrosive.		
Main hazards	Harmful by inhalation, in contact with skin and if swallowed. Causes burns. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.		
2.1.2. Classification - EC 1272/2008	Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Acute Tox. 4: H332; Aquatic Chronic 3: H412;		

competent person

2.2. Label elements	
Hazard pictograms	
Signal Word	Danger
Hazard Statement	Acute Tox. 4: H302 - Harmful if swallowed.
	Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
	Skin Sens. 1: H317 - May cause an allergic skin reaction.
	Acute Tox. 4: H332 - Harmful if inhaled.
	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Precautionary Statement:	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
Prevention	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
	P264 - Wash thoroughly after handling.

Revision 0 Revision date 2018-10-16

#### 2.2. Label elements

	P270 - Do no eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.			
	P272 - Contaminated work clothing should not be allowed out of the workplace.			
	P273 - Avoid release to the environment.			
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.			
Precautionary Statement:	P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ /if you feel unwell.			
Response	P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.			
	P302+P352 - IF ON SKIN: Wash with plenty of water/ .			
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse			
	skin with water/shower.			
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact			
	lenses, if present and easy to do. Continue rinsing.			
	P310 -Immediately call a POISON CENTER/doctor/ .			
	P312 - Call a POISON CENTER/doctor/ /if you feel unwell.			
	P321 - Specific treatment (see on this label).			
	P330 - Rinse mouth.			
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.			
	P363 - Wash contaminated clothing before reuse.			
Precautionary Statement:	P405 - Store locked up.			
Storage				
Precautionary Statement:	P501 - Dispose of contents/container to			
Disposal				

#### 2.3. Other hazards

Other hazards	No data is available on this product.

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

#### 67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
3-Aminomethyl-3,5,5-trimethylcyclo hexylamine	612-067-00-9	2855-13-2	220-666-8	01-2119514687-32	30 - 40%	Xn; R21/22 C; R34 R43 R52/53	
Benzyl alcohol	603-057-00-5	100-51-6	202-859-9	01-2119492630-38	30 - 40%	Xn; R20/22	
m-xylylenediamine		1477-55-0	216-032-5	01-2119480150-50	10 - 20%		

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
3-Aminomethyl-3,5,5-trimethylcyclo hexylamine	612-067-00-9	2855-13-2	220-666-8	01-2119514687-32	30 - 40%	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412;	
Benzyl alcohol	603-057-00-5	100-51-6	202-859-9	01-2119492630-38	30 - 40%	Acute Tox. 4: H332; Acute Tox. 4: H302;	
m-xylylenediamine		1477-55-0	216-032-5	01-2119480150-50	10 - 20%	Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Acute Tox. 4: H332; Aquatic Chronic 3: H412;	

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.	
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.	
Ingestion	Move the exposed person to fresh air. Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.	



Revision 0 Revision date 2018-10-16

	Revision date 2018-10-1
4.2. Most important symptoms	s and effects, both acute and delayed
Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	Risk of serious damage to eyes.
Skin contact	May cause irritation to skin.
Ingestion	Seek medical attention.
4.3. Indication of any immedia	te medical attention and special treatment needed
Inhalation	If you feel unwell, seek medical advice (show the label where possible).
Eye contact	Seek medical attention.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention.
SECTION 5: Firefighting m	neasures
5.1. Extinguishing media	
	Use extinguishing media appropriate to the surrounding fire conditions. Carbon oxides. Dry chemical. Foam. Do NOT use water jet.
5.2. Special hazards arising fr	om the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Wear self contained breathing apparatus and protective clothing.
Further information	
	Dispose of as special waste in compliance with official regulations.
SECTION 6: Accidental re	lease measures
6.1. Personal precautions, pro	otective equipment and emergency procedures
	Ensure adequate ventilation of the working area. Avoid contact with skin and eyes.
6.2. Environmental precaution	
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for	
	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
6.4. Reference to other section	ns
	See section 8 for further information. See section 13 for further information.
SECTION 7: Handling and	storage
7.1. Precautions for safe hand	
	Ensure adequate ventilation of the working area. Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.
7.2. Conditions for safe storage	ge, including any incompatibilities
	Keep containers tightly closed. Keep in a cool, dry, well ventilated area. Store in correctly labelled containers.
7.3. Specific end use(s)	
. ,,	See section 1.2. Relevant identified uses of the substance or mixture and uses advised against for further information.
SECTION 8: Exposure cor	ntrols/personal protection



8.1. Control parameters

Revision Revision date 2018-10-16

#### 8.1. Control parameters

This product does not contain any relevant quantities of materials with critical values that have to be monitored in the workplace.

WEL-8hr Limit - 90mg/m3, (Benzyl Alcohol).

#### 8.2. Exposure controls







8.2.1. Appropriate engineering controls

8.2.2. Individual protection measures

Eye / face protection

Skin protection -Handprotection

Skin protection - Other

Respiratory protection

Occupational exposure controls

Ensure adequate ventilation of the working area.

Wear protective clothing

Approved safety goggles.

Wear suitable gloves.

Wear suitable protective clothing.

Wear suitable respiratory equipment when necessary.

Keep away from food, drink and animal feedingstuffs.

#### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance Liquid

> Colour Black

Odour Characteristic

Нα

No data available

Melting point

No data available

Freezing Point > 200 °C

No data available

Initial boiling point

Flash point 100 °C

**Evaporation rate** 

No data available

Flammability (solid, gas)

No data available

Vapour pressure

10 Pa

Vapour density

No data available

Relative density

1.06 (H2O = 1 @ 20 °C)

**Fat Solubility** 

No data available

Partition coefficient

No data available

Autoignition temperature

380 °C

Viscosity

200 mPas (Cone & Plate)

Explosive properties

No data available

Oxidising properties Solubility

No data available Insoluble in water

9.2. Other information



Revision 0 Revision date 2018-10-16

#### 9.2. Other information

Conductivity
Surface tension
Gas group
Benzene Content
Lead content
VOC (Volatile organic

No data available
No data available
0 %
0 %

#### SECTION 10: Stability and reactivity

compounds)

#### 10.1. Reactivity

Stable under normal conditions.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Reacts with. Acids. Alkalis. Oxidising agents.

#### 10.4. Conditions to avoid

No data is available on this product.

#### 10.5. Incompatible materials

Strong oxidising agents.

#### 10.6. Hazardous decomposition products

No data is available on this product.

#### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

May cause severe irritation to skin, eyes and mucous membranes.	
Risk of serious damage to eyes. Strong caustic effect.	
May cause sensitisation by skin contact.	
No mutagenic effects reported.	
No observed effect level. No teratogenic effects reported.	

#### 11.1.4. Toxicological Information

3-Aminomethyl-3,5,5-trimethylcy	Dermal Rat LD50: >2000mg/kg	<b>Oral Rat LD50:</b> 1030mg/kg
clohexylamine		
	Dermal Rabbit LD50: 1840mg/kg	
Benzyl alcohol	Oral Rat LD50: 1230mg/kg	Dermal Rabbit LD50: 2000mg/kg

#### 11.1.13. Other information

Swallowing will lead to a strong caustic effect on mouth and throat and danger of perforation of esophagus and stomach.

#### SECTION 12: Ecological information

#### 12.1. Toxicity

3-Aminomethyl-3,5,5-trimethylcy clohexylamine	Daphnia EC50/48h: 23 mg/l	Algae IC50/72h: 50.0000 mg/l
Benzyl alcohol	Fish LC50/96h: 110.0000 mg/l  Daphnia EC50/48h: 400.0000 mg/l	Algae IC50/72h: 640.0000 mg/l
	Fish LC50/96h: 645.0000 mg/l	



Revision 0 Revision date 2018-10-16

12.2. Persistence and degradal	bility
	No data is available on this product.
PBT	
	Not applicable.
12.3. Bioaccumulative potential	
	No data is available on this product.
Partition coefficient	
	Reprotec Floor Doctor Rapid - No data available
	Curing Agent
12.4. Mobility in soil	
	No data is available on this product.
12.5. Results of PBT and vPvB	assessment
	No data is available on this product.
12.6. Other adverse effects	
	No data is available on this product.
SECTION 13: Disposal con	siderations
13.1. Waste treatment methods	<b>3</b>
	Dispose of in compliance with all local and national regulations.
General information	
	08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS.  08 02 wastes from MFSU of other coatings (including ceramic materials).  08 02 99 wastes not otherwise specified.
Disposal methods	•
	The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers.
Disposal of packaging	
	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers.

### **SECTION 14: Transport information**

#### Hazard pictograms





Revision 0
Revision date 2018-10-16

	Revision date 2018-10-16
14.1. UN number	
	UN2735
14.2. UN proper shipping name	
	AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine)
14.3. Transport hazard class(es)	)
ADR/RID	8
Subsidiary risk	-
IMDG	8
Subsidiary risk	-
IATA	8
Subsidiary risk	-
14.4. Packing group	
Packing group	
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
14.6. Special precautions for user	
	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of a spillage.
14.7. Transport in bulk according	g to Annex II of MARPOL 73/78 and the IBC Code
	For transport approval see regulatory information.
ADR/RID	
Hazard ID	80
Tunnel Category	(E)
IMDG	
EmS Code	F-A S-B
IATA	
Packing Instruction (Cargo)	856
Maximum quantity	60 L
Packing Instruction (Passenger)	852
Maximum quantity	5 L

#### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL
	of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of
	Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC
	and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94
	as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC,
	93/105/EC and 2000/21/EC.

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.



Revision 0 Revision date 2018-10-16

15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

#### SECTION 16: Other information

#### Other information

Text of risk phrases in Section R20/22 - Harmful by inhalation and if swallowed. 3 R21/22 - Harmful in contact with skin and if swallowed. R34 - Causes burns. R43 - May cause sensitisation by skin contact. R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Text of Hazard Statements in Acute Tox. 4: H302 - Harmful if swallowed. Section 3 Acute Tox. 4: H312 - Harmful in contact with skin. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Sens. 1: H317 - May cause an allergic skin reaction. Aguatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Acute Tox. 4: H332 - Harmful if inhaled. Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled 0 g/l.

Maximum content of VOC

#### **Further information**

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

