

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Reprotec Griplite - Base

Page 1/8

Revision 0 Revision date 2018-10-11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier			
Product name	Reprotec Griplite - Base		
1.2. Relevant identified uses of t	he substance or mixture and uses advised against		
Product Use	 [SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing; [SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a] Coatings and paints, thinners, paint removers; [PROC11] Non industrial spraying; [SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a] 		
	Coatings and paints, thinners, paint removers; [PROC7] Industrial spraying;		
1.3. Details of the supplier of the	safety data sheet		
Company	RM Suppliers Ltd		
Address	38 High Street North		
	Langley Moor		
	County Durham		
	DH7 8JG		
Web	www.rmsuppliers.com		
Telephone	0191 3897067		
Email address of the	sales@rmsuppliers.com		
competent person			
SECTION 2: Hazards identification			

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411;
2.2. Label elements	
Hazard pictograms	
Signal Word	Warning
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation.
	Skin Sens. 1: H317 - May cause an allergic skin reaction.
	Eye Irrit. 2: H319 - Causes serious eye irritation.
	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Precautionary Statement:	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
Prevention	P264 - Wash thoroughly after handling.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
	P273 - Avoid release to the environment.



2.2. Label elements		
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.	
Precautionary Statement:	P302+P352 - IF ON SKIN: Wash with plenty of water/ .	
Response	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact	
	lenses, if present and easy to do. Continue rinsing.	
	P321 - Specific treatment (see on this label).	
	P332+P313 - If skin irritation occurs: Get medical advice/attention.	
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.	
	P337+P313 - If eye irritation persists: Get medical advice/attention.	
	P391 - Collect spillage.	
Precautionary Statement:	P501 - Dispose of contents/container to	
Disposal		
2.3. Other hazards		
Other hazards	No data is available on this product.	

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Bisphenol A-(epichlorhydrin) (reaction product)	603-074-00-8	25068-38-6	500-033-5	01-2119456619-26	50 - 60%	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411;
bisphenol F-epoxy resin		9003-36-5	500-006-8	01-2119454392-40	10 - 20%	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411;
Oxiran, Mono[(C12-14- alkyloxy)methyl]- derivative	603-103-00-4	68609-97-2	271-846-8	01-2119485289-22	1 - 10%	Skin Irrit. 2: H315; Skin Sens. 1: H317;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.	
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.	
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.	
4.2. Most important symptoms and effects, both acute and delayed		

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.	
Eye contact	May cause irritation to eyes.	
Skin contact	May cause irritation to skin.	
Ingestion	Ingestion may cause nausea and vomiting.	
4.3. Indication of any immediate medical attention and special treatment needed		
Inhalation	Seek medical attention if irritation or symptoms persist.	
Eye contact	Seek medical attention if irritation or symptoms persist.	
Skin contact	Seek medical attention if irritation or symptoms persist.	

Ingestion If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Use extinguishing media appropriate to the surrounding fire conditions. Carbon oxides. Dry chemical. Foam. Do NOT use water jet.

5.2. Special hazards arising from the substance or mixture



5.2. Special hazards arising fror	n the substance or mixture	
C. A. daile a fan Graffachtana	Burning produces irritating, toxic and ob	loxious lumes.
5.3. Advice for firefighters		
	Wear self contained breathing apparatus sewers or drains.	s and protective clothing. Do not allow runoff water to enter
SECTION 6: Accidental relea	ase measures	
6.1. Personal precautions, prote	ective equipment and emergency procedure	əs
	Ensure adequate ventilation of the work	ng area. Avoid contact with skin and eyes.
6.2. Environmental precautions	·	
	Do not allow product to enter drains. Do safe.	not flush into surface water. Prevent further spillage if
6.3. Methods and material for co	ontainment and cleaning up	
	Transfer to suitable, labelled containers water.	for disposal. Clean spillage area thoroughly with plenty of
6.4. Reference to other sections	;	
	See section 8 for further information. See section 13 for further information.	
SECTION 7: Handling and s	torage	
7.1. Precautions for safe handlin	•	
		ng area. Avoid contact with eyes and skin. Adopt best
	Manual Handling considerations when h	
7.2. Conditions for safe storage,	including any incompatibilities	
	Keep containers tightly closed. Keep in a containers.	a cool, dry, well ventilated area. Store in correctly labelled
7.3. Specific end use(s)		
	See section 1.2. Relevant identified user further information.	s of the substance or mixture and uses advised against for
SECTION 8: Exposure contr	ols/personal protection	
8.1. Control parameters		
	workplace atmosphere or biological mor the ventilation or other control measures equipment. Reference should be made t	oduct contains ingredients with exposure limits, personal, intoring may be required to determine the effectiveness of and/or the necessity to use respiratory protective o European Standard EN 689 for methods of the o chemical agents and national guidance documents for ous substances.
8.1.1. Exposure Limit Values		
Bisphenol A-(epichlorhydrin) (reaction product)	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 12.3
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total	WEL 15 min limit mg/m3 total
	inhalable dust: WEL 8-hr limit mg/m3 total	inhalable dust: WEL 15 min limit mg/m3 total

respirable dust:

8.2. Exposure controls



respirable dust:

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Butyl rubber gloves. Chemical resistant gloves. Polyvinyl chloride - PVC ().
Skin protection - Other	Wear suitable protective clothing.
Respiratory protection	Wear suitable respiratory equipment when necessary.
Occupational exposure controls	Keep away from food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Various
Odour	Slight
Initial boiling point	100 °C
Flash point	130 °C
Relative density	1.13 (H2O = 1 @ 20 °C)
Viscosity	700 mPas (Cone & Plate)
pH	No data available
Melting point	No data available
Freezing Point	No data available
Explosive properties	No data available
Oxidising properties	No data available
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper Explosive Limit	No data available
Lower Explosive Limit	
	No data available
Vapour density	No data available
Solubility	Slightly soluble in water

9.2. Other information

Benzene Content	0 %
Lead content	0 %
VOC (Volatile organic	0 g/l
compounds)	
Conductivity	No data available
Surface tension	No data available
Gas group	No data available

SECTION 10: Stability and reactivity



 Revision
 0

 Revision date
 2018-10-11

10.1. Reactivity			
	Stable under normal conditions.		
10.2. Chemical stability			
	Stable under normal conditions.		
10.3. Possibility of hazardous re	pactions		
	No data is available on this product.		
10.4. Conditions to avoid	• · · ·		
	Heat will increase pressure in sealed containers.		
10.5. Incompatible materials	<u> </u>		
	Carbon oxides.		
10.6. Hazardous decomposition	products		
	Will not decompose if stored and used as recommended.		
SECTION 11: Toxicological	information		
11.1. Information on toxicologica	al effects		
Skin corrosion/irritation	May cause irritation to skin.		
Serious eye damage/irritation	May cause irritation to eyes.		
Respiratory or skin sensitisation	May cause sensitisation by skin contact.		
Germ cell mutagenicity	No mutagenic effects reported.		
Carcinogenicity	No carcinogenic effects reported.		
Reproductive toxicity	No observed effect level. No teratogenic effects reported.		
Repeated or prolonged exposure	Once sensitised, an allergic reaction may occur when subs	sequently exposed to very low levels.	
11.1.4. Toxicological Information	n		
Bisphenol A-(epichlorhydrin)	Dermal Rat LD50: >2000mg/kg	Oral Rat LD50: >2000mg/kg	
(reaction product)	Inhalation Rat LC50/4 h: >0.15mg/l		
bisphenol F-epoxy resin	Dermal Rat LD50: >2000mg/kg	Oral Rat LD50: >5000mg/kg	
		· · ·	
SECTION 12: Ecological info	ormation		
12.1. Toxicity			
Bisphenol A-(epichlorhydrin)	Daphnia EC50/48h: 1.7000 mg/l	Algae IC50/72h: 9.4000 mg/l	
(reaction product)	Fish LC50/96h: 1.5000 mg/l		
bisphenol F-epoxy resin	Daphnia EC50/48h: 1.6000 mg/l	Algae IC50/72h: 1.8000 mg/l	
	Fish LC50/96h: 0.5500 mg/l	Algae EC50/72h: 1.8	
12.2. Persistence and degradab	hility		
	Not readily biodegradable.		
12.3. Bioaccumulative potential	Not readily blodegradable.		
	Low.		
Partition coefficient	1 - Con.		



Reprotec Griplite - Base No data available

	Revision date 2018-10-11
12.4. Mobility in soil	
	No data is available on this product.
12.5. Results of PBT and vPvB a	assessment
	No data is available on this product.
12.6. Other adverse effects	
	No data is available on this product.
SECTION 13: Disposal cons	iderations
13.1. Waste treatment methods	
	Dispose of in compliance with all local and national regulations.
General information	
	08 02 99 wastes not otherwise specified.
Disposal methods	
	The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers.
Disposal of packaging	
	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers.
SECTION 14: Transport info	rmation
Hazard pictograms	
14.1. UN number	•
	UN3082
14.2. UN proper shipping name	·
	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A-Epoxy Resin)
14.3. Transport hazard class(es))
ADR/RID	9
Subsidiary risk	

9

-9

-

Ш

IMDG

IATA

Subsidiary risk

Subsidiary risk

Packing group

14.4. Packing group



14.5. Environmental hazards	
Environmental hazards	Yes
Marine pollutant	Yes
14.6. Special precautions for user	
	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of a spillage.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	
	For transport approval see regulatory information.
ADR/RID	
Hazard ID	90
Tunnel Category	(E)
IMDG	
EmS Code	F-A S-F
IATA	
Packing Instruction (Cargo)	964
Maximum quantity	450 L
Packing Instruction	964
(Passenger)	
Maximum quantity	450 L
SECTION 15: Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
15.2. Chemical safety assessment	
	This product contains substances for which Chemical Safety Assessments are still required.
SECTION 16: Other information	
Other information	
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Maximum content of VOC	0 g/l.
Further information	



 Revision
 0

 Revision date
 2018-10-11

Further information

combination with any other materials or in any other process.

