

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/8

Reprotec Griplite - Curing Agent

Revision Revision date 2018-10-16

SECTION 1: Identification of the substance/mixture and of the com	pany/undertaking
---	------------------

1.1. Product identifier

Product name	Reprotec Griplite - Curing Agent
--------------	----------------------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services,
	craftsmen); [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or
	brushing; [ERC2] Formulation of preparations;

1.3. Details of the supplier of the safety data sheet

Company	RM Suppliers Ltd
Address	38 High Street North
	Langley Moor

County Durham DH7 8JG

Web www.rmsuppliers.com

Telephone 0191 3897067

Email address of the competent person

sales@rmsuppliers.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC	Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Acute Tox. 4: H332; Aquatic
1272/2008	Chronic 3: H412;

2.2. Label elements

Hazard pictograms





Signal Word

Danger

Hazard Statement Acute Tox. 4: H302 - Harmful if swallowed.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statement:

Prevention

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash thoroughly after handling.

P270 - Do no eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Revision 1
Revision date 2018-10-16

2.2. Label elements

Precautionary Statement:	P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ /if you feel unwell.		
Response	P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.		
	P302+P352 - IF ON SKIN: Wash with plenty of water/ .		
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse		
	skin with water/shower.		
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact		
	lenses, if present and easy to do. Continue rinsing.		
	P310 -Immediately call a POISON CENTER/doctor/ .		
	P312 - Call a POISON CENTER/doctor/ /if you feel unwell.		
	P321 - Specific treatment (see on this label).		
	P330 - Rinse mouth.		
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.		
	P363 - Wash contaminated clothing before reuse.		
Precautionary Statement:	P405 - Store locked up.		
Storage			
Precautionary Statement:	P501 - Dispose of contents/container to		
Disposal			
2.3. Other hazards			

2.3. Other hazards

Other hazards No data is available on this product.	
---	--

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
3-Aminomethyl-3,5,5-trimethylcyclo hexylamine	612-067-00-9	2855-13-2	220-666-8	01-2119514687-32	30 - 40%	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412;
Benzyl alcohol	603-057-00-5	100-51-6	202-859-9	01-2119492630-38	20 - 30%	Acute Tox. 4: H332; Acute Tox. 4: H302;
m-xylylenediamine		1477-55-0	216-032-5	01-2119480150-50	10 - 20%	Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Acute Tox. 4: H332; Aquatic Chronic 3: H412;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.	
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.	
Ingestion	Move the exposed person to fresh air. Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.	

4.2. Most important symptoms and effects, both acute and delayed

	,
Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	Risk of serious damage to eyes.
Skin contact	May cause irritation to skin.
Ingestion	Seek medical attention.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	If you feel unwell, seek medical advice (show the label where possible).		
Eye contact	Seek medical attention.		
Skin contact	Seek medical attention if irritation or symptoms persist.		

4.3. Indication of any immediat	te medical attention and special treatment needed
Ingestion	Seek medical attention.
SECTION 5: Firefighting m	easures
5.1. Extinguishing media	
	Use extinguishing media appropriate to the surrounding fire conditions. Carbon oxides. Dry chemical. Foam. Do NOT use water jet.
5.2. Special hazards arising fro	om the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Wear self contained breathing apparatus and protective clothing.
Further information	
	Dispose of as special waste in compliance with official regulations.
SECTION 6: Accidental rele	ease measures
6.1. Personal precautions, prof	tective equipment and emergency procedures
	Ensure adequate ventilation of the working area. Avoid contact with skin and eyes.
6.2. Environmental precautions	3
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for o	containment and cleaning up
	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
6.4. Reference to other section	is .
	See section 8 for further information. See section 13 for further information.
SECTION 7: Handling and	storage
7.1. Precautions for safe hand	ling
	Ensure adequate ventilation of the working area. Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.
7.2. Conditions for safe storage	e, including any incompatibilities
	Keep containers tightly closed. Keep in a cool, dry, well ventilated area. Store in correctly labelled containers.
7.3. Specific end use(s)	
	See section 1.2. Relevant identified uses of the substance or mixture and uses advised against for further information.
SECTION 8: Exposure con	trols/personal protection
8.1. Control parameters	
	This product does not contain any relevant quantities of materials with critical values that have to be monitored in the workplace. WEL-8hr Limit - 90mg/m3, (Benzyl Alcohol).
8.2. Exposure controls	

Revision 1
Revision date 2018-10-16

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection	Wear protective clothing.
measures	
Eye / face protection	Approved safety goggles.
Skin protection -	Wear suitable gloves.
Handprotection	
Skin protection - Other	Wear suitable protective clothing.
Respiratory protection	Wear suitable respiratory equipment when necessary.
Occupational exposure	Keep away from food, drink and animal feedingstuffs.
controls	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Light yellow
Odour	Characteristic
Flash point	100 °C
Vapour pressure	10 Pa
Autoignition temperature	380 °C
Viscosity	200 mPas (Cone & Plate)
Relative density	1.06 (H2O = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	No data available
Explosive properties	No data available
Oxidising properties	No data available
Vapour density	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
pH	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	> 200 °C
Solubility	Insoluble in water

9.2. Other information

Benzene Content	0 %
Lead content	0 %
VOC (Volatile organic	
compounds)	
Conductivity	No data available
Surface tension	No data available
Gas group	No data available

SECTION 10: Stability and reactivity

1	n	۱ 1	1	R	ea	cti	ivi	it.	,
	u	٠. ١	١.	г	Сa	Cu	v	LV	7

	Stable under normal conditions.
10.2. Chemical stability	
	Stable under normal conditions

10.3. Possibility of hazardous reactions

10.3. Possibility of hazardous re	actions	
	Reacts with. Acids. Alkalis. Oxidising agents.	
0.4. Conditions to avoid		
	No data is available on this product.	
10.5. Incompatible materials		
	Strong oxidising agents.	
10.6. Hazardous decomposition	products	
	No data is available on this product.	
SECTION 11: Toxicological	information	
11.1. Information on toxicologica		
Skin corrosion/irritation Serious eye damage/irritation	May cause severe irritation to skin, eyes and mucous membrar Risk of serious damage to eyes. Strong caustic effect.	nes.
Respiratory or skin	May cause sensitisation by skin contact.	
sensitisation	May dadde denomination by drift dentact.	
Germ cell mutagenicity	No mutagenic effects reported.	
Reproductive toxicity	No observed effect level. No teratogenic effects reported.	
11.1.4. Toxicological Information	1	
3-Aminomethyl-3,5,5-trimethylcy	Dermal Rat LD50: >2000mg/kg	Oral Rat LD50: 1030mg/kg
clohexylamine	Dermal Rabbit LD50: 1840mg/kg	
Benzyl alcohol		Dermal Rabbit LD50: 2000mg/kg
11.1.13. Other information		
11.1.13. Other information	Swallowing will lead to a strong caustic effect on mouth and the	roat and danger of perforation of
11.1.13. Other information	Swallowing will lead to a strong caustic effect on mouth and the esophagus and stomach.	roat and danger of perforation of
11.1.13. Other information SECTION 12: Ecological info	esophagus and stomach.	roat and danger of perforation of
	esophagus and stomach.	roat and danger of perforation of
SECTION 12: Ecological info	esophagus and stomach.	roat and danger of perforation of Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info	esophagus and stomach. Drmation Daphnia EC50/48h: 23 mg/l	
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine	esophagus and stomach. Daphnia EC50/48h: 23 mg/l Fish LC50/96h: 110.0000 mg/l	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy	esophagus and stomach. Drmation Daphnia EC50/48h: 23 mg/l	
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine Benzyl alcohol	esophagus and stomach. Daphnia EC50/48h: 23 mg/l Fish LC50/96h: 110.0000 mg/l Daphnia EC50/48h: 400.0000 mg/l Fish LC50/96h: 645.0000 mg/l	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine	esophagus and stomach. Daphnia EC50/48h: 23 mg/l Fish LC50/96h: 110.0000 mg/l Daphnia EC50/48h: 400.0000 mg/l Fish LC50/96h: 645.0000 mg/l	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine Benzyl alcohol	esophagus and stomach. Daphnia EC50/48h: 23 mg/l Fish LC50/96h: 110.0000 mg/l Daphnia EC50/48h: 400.0000 mg/l Fish LC50/96h: 645.0000 mg/l	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine Benzyl alcohol	Daphnia EC50/48h: 23 mg/l	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine Benzyl alcohol 12.2. Persistence and degradab	Daphnia EC50/48h: 23 mg/l	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine Benzyl alcohol 12.2. Persistence and degradab	esophagus and stomach. Daphnia EC50/48h: 23 mg/l Fish LC50/96h: 110.0000 mg/l Daphnia EC50/48h: 400.0000 mg/l Fish LC50/96h: 645.0000 mg/l Fish LC50/96h: 645.0000 mg/l	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine Benzyl alcohol 12.2. Persistence and degradab	esophagus and stomach. Daphnia EC50/48h: 23 mg/l Fish LC50/96h: 110.0000 mg/l Daphnia EC50/48h: 400.0000 mg/l Fish LC50/96h: 645.0000 mg/l Fish LC50/96h: 645.0000 mg/l	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine Benzyl alcohol 12.2. Persistence and degradab	esophagus and stomach. Daphnia EC50/48h: 23 mg/l Fish LC50/96h: 110.0000 mg/l Daphnia EC50/48h: 400.0000 mg/l Fish LC50/96h: 645.0000 mg/l Fish LC50/96h: 645.0000 mg/l	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine Benzyl alcohol 12.2. Persistence and degradab	esophagus and stomach. Daphnia EC50/48h: 23 mg/l Fish LC50/96h: 110.0000 mg/l Daphnia EC50/48h: 400.0000 mg/l Fish LC50/96h: 645.0000 mg/l Sility No data is available on this product. Not applicable.	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine Benzyl alcohol 12.2. Persistence and degradab PBT 12.3. Bioaccumulative potential	esophagus and stomach. Daphnia EC50/48h: 23 mg/l Fish LC50/96h: 110.0000 mg/l Daphnia EC50/48h: 400.0000 mg/l Fish LC50/96h: 645.0000 mg/l Sility No data is available on this product. Not applicable.	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine Benzyl alcohol 12.2. Persistence and degradab PBT 12.3. Bioaccumulative potential	esophagus and stomach. Daphnia EC50/48h: 23 mg/l Fish LC50/96h: 110.0000 mg/l Daphnia EC50/48h: 400.0000 mg/l Fish LC50/96h: 645.0000 mg/l Fish LC50/96h: 645.0000 mg/l No data is available on this product. Not applicable. No data is available on this product.	Algae IC50/72h: 50.0000 mg/l
SECTION 12: Ecological info 12.1. Toxicity 3-Aminomethyl-3,5,5-trimethylcy clohexylamine Benzyl alcohol 12.2. Persistence and degradab PBT 12.3. Bioaccumulative potential	esophagus and stomach. Daphnia EC50/48h: 23 mg/l Fish LC50/96h: 110.0000 mg/l Daphnia EC50/48h: 400.0000 mg/l Fish LC50/96h: 645.0000 mg/l Fish LC50/96h: 645.0000 mg/l No data is available on this product. Not applicable. No data is available on this product.	Algae IC50/72h: 50.0000 mg/l

No data is available on this product. SECTION 13: Disposal considerations 13.1. Waste treatment methods Dispose of in compliance with all local and national regulations. General information 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS. 08 02 wastes from MFSU of other coatings (including ceramic materials). 08 02 9 wastes from MFSU of other coatings (including ceramic materials). 08 02 9 wastes from WFSU of other coatings (including ceramic materials). 08 02 9 wastes from WFSU of other coatings (including ceramic materials). 08 02 99 wastes not otherwise specified. Disposal methods The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products a local waste comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of split material and runoff and contact sith soil, waterways, drains and sewers. Disposal of packaging Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers. SECTION 14: Transport information LUN2735 14.1. UN number AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine)		Revision date 2018-10-16
No data is available on this product.	12.5. Results of PBT and vPvB a	assessment
No data is available on this product.		No data is available on this product.
SECTION 13: Disposal considerations 13.1. Waste treatment methods Dispose of in compliance with all local and national regulations. General Information 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS. 08 02 wastes from MFSU of other coatings (including ceramic materials). 08 02 99 wastes from MFSU of other coatings (including ceramic materials). 08 102 wastes from MFSU of other coatings (including ceramic materials). 08 102 wastes from MFSU of other coatings (including ceramic materials). 08 102 wastes from MFSU of other coatings (including ceramic materials). 09 102 99 wastes not otherwise specified. Disposal methods The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products waste disposal contractor. Disposal of this product, solutions and any by product would at all times comply with the requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of split material and runoff and contact sith soil, waterways, drains and sewers. Disposal of packaging Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers. SECTION 14: Transport information LUN2735 14.1. UN number AMINES, LIQUID, CORROSIVE N.O.S. (12.6. Other adverse effects	
Dispose of in compliance with all local and national regulations. General information 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS. 08 02 wastes from MFSU of other coatings (including ceramic materials). 08 02 99 wastes not otherwise specified. Disposal methods The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empited containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers. Disposal of packaging Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers. SECTION 14: Transport information Hazard pictograms 14.1. UN number UN2735 AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine)		No data is available on this product.
Dispose of in compliance with all local and national regulations. General information 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS. 08 02 wastes from MFSU of other coatings (including ceramic materials). 08 02 99 wastes not otherwise specified. Disposal methods The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste loss designation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empited containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of split material and runoff and contact sith soil, waterways, drains and sewers. Disposal of packaging Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers. SECTION 14: Transport information Hazard pictograms 4.1.1. UN number UN2735 14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine)	SECTION 13: Disposal cons	iderations
Dispose of in compliance with all local and national regulations. General information 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS. 08 02 wastes from MFSU of other coatings (including ceramic materials). 08 02 99 wastes not otherwise specified. Disposal methods The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of split material and runoff and contact sith soil, waterways, drains and sewers. Disposal of packaging Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers. SECTION 14: Transport information Hazard pictograms 14.1. UN number UN2735 14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine)	-	
General Information 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS. 08 02 wastes from MFSU of other coatings (including ceramic materials). 08 02 wastes not otherwise specified. Disposal methods The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers. Disposal of packaging Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers. SECTION 14: Transport information Hazard pictograms 14.1. UN number UN2735 14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine)	10.1. Waste treatment metrous	Dispose of in compliance with all local and national regulations
08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS. 08 02 wastes from MFSU of other coatings (including ceramic materials). 08 02 99 wastes not otherwise specified. The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste isposal eligislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers. Disposal of packaging	Constal information	Dispose of in compilance with an local and national regulations.
The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers. Disposal of packaging Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers. SECTION 14: Transport information Hazard pictograms UN2735 14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine)		COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS. 08 02 wastes from MFSU of other coatings (including ceramic materials).
The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and my by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers. Disposal of packaging Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers. SECTION 14: Transport information Hazard pictograms UN2735 14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine)	Disposal methods	
Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers. SECTION 14: Transport information Hazard pictograms UN2735 14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine) 14.3. Transport hazard class(es)		of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and
Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers. SECTION 14: Transport information Hazard pictograms UN2735 14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine) 14.3. Transport hazard class(es)	Disposal of packaging	
SECTION 14: Transport information Hazard pictograms 14.1. UN number UN2735 14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine) 14.3. Transport hazard class(es)	, , ,	and national provisions. Do not empty into drains, dispose of this material and its container at
Hazard pictograms 14.1. UN number UN2735 14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine) 14.3. Transport hazard class(es)	SECTION 14: Transport info	rmation
14.1. UN number UN2735 14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine) 14.3. Transport hazard class(es)		
14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine) 14.3. Transport hazard class(es)	nazaru piciograms	
14.2. UN proper shipping name AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine) 14.3. Transport hazard class(es)	14.1. UN number	
AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine) 14.3. Transport hazard class(es)		UN2735
14.3. Transport hazard class(es)	14.2. UN proper shipping name	
		AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine)
ADD/DID	14.3. Transport hazard class(es)	
ADR/RID 8	ADR/RID	8
Subsidiary risk -	Subsidiary risk	-
IMDG 8	IMDG	8
Subsidiary risk -	•	-
	IATA	8
Subsidiary risk -	•	-
14.4. Packing group	14.4. Packing group	

Revision 1
Revision date 2018-10-16

	1-1-1-1-1
14.4. Packing group	
Packing group	III
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
14.6. Special precautions for use	er
	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of a spillage.
14.7. Transport in bulk according	g to Annex II of MARPOL 73/78 and the IBC Code
	For transport approval see regulatory information.
ADR/RID	
Hazard ID	80
Tunnel Category	(E)
IMDG	
EmS Code	F-A S-B
IATA	
Packing Instruction (Cargo)	856
Maximum quantity	60 L
Packing Instruction	852
(Passenger) Maximum quantity	5 L
SECTION 15: Pegulatory inf	ormation

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

_	
Reall	lations
ı vogu	auono

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:. 12 - 12.1. Toxicity.
Text of Hazard Statements in	Acute Tox. 4: H302 - Harmful if swallowed.
Section 3	Acute Tox. 4: H312 - Harmful in contact with skin.
	Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
	Skin Sens. 1: H317 - May cause an allergic skin reaction.
	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
	Acute Tox. 4: H332 - Harmful if inhaled.

Other information	
	Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled
Maximum content of VOC	0 g/l.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.