

The Resin Mill (Primer C Pro) (A1408)

Polyurethane Floor Sealer and Primer

(A1408) has been developed as a floor sealer or primer for polyurethane coatings. (A1408) seals and primers concrete prior to the application of floor coatings and aggregate bound systems.

Benefits:

Fast-Curing.
Simple Application.
Multi-Purpose Product.

Technical Data

Base	Polyurethane	Drying -Time	90 minutes @ 20°C
Appearance	Brown thin liquid	Shelf Life	6 months @ 5-25°C
Temperature Resistance	N/A	Storage	Unopened 5-25°C
Coverage	20m² / ltr	Environmental	See MSDS
Application Temperature	5°-25°C	Cleaner	Solvent 1
Viscosity CPS	15 cps		

Instructions for Use:

Preparation/priming

1. Ensure all substrates are clean, dry and free from contamination.

Application

- 1. (A1408) can be applied by brush or roller to a clean, dry concrete substrate, including felt, asphalt and concrete.
- 2. Allow to dry for 2 hours before applying the aggregate bound system.





The Resin Mill (Primer C Pro) (A1408)

General Notes

This product is based on MDI which means it will discolour if exposed to UV light. Consumption rates given are indicative only and all substrates should be treated on an individual basis.

IMPORTANT NOTES

Storage and handling: The product should be stored unopened in a dry condition at a temperature of 5-25°C. This will ensure the stated shelf-life. The adhesive will have a limited life once the container is opened.

Temperature and timings: All information on temperature and timings represent normal working conditions and is provided as a guideline only. However, please contact us for advice if you wish to operate outside of these parameters.

Disclaimer: We have taken care to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact us to check whether there have been any changes to the information since publication of the literature. Please ensure you have read the hazard labels and material safety data sheet before using this product.

