



Kiesol MB

Special primer



Availability			
Quantity per pallet	90	60	24
Packaging unit	5 l	10 l	30 l
Type of container	Plastic canister	Plastic canister	Plastic canister
Container code	05	10	30
Art. no.			
3008	■	■	■

Application rate

Approx. 100-200 ml/m² depending on the substrate

Apply to a large enough trial area to determine the precise amount required.



Range of use

- System component for waterproofing of buildings
- Suitable for absorbent mineral substrates



Property profile

- Improves adhesion
- Repels water
- Strengthens



Characteristic data of the product

Density (20 °C)	1.01 g/cm ³
pH value	11
Appearance	milky

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Certificates

- **Remmers International Guarantee**
Inasmuch as a Remmers International Guarantee (RIG) has been granted, only the conditions / requirements indicated in the written contract between the RIG specialist firm and Remmers shall apply.

Possible system products




- **MB 2K (3014)**
- **Remmers PMBCs**
- **Remmers Waterproofing Grouts**

Preparation

- **Substrate requirements**
The substrate must be dry, clean, load-bearing and free of dust.

Directions



- **Conditions for use**
Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C

Apply evenly to the material using a brush, roller or spray.
Make sure that no pools form.

Notes

Deviations from applicable regulations must be agreed separately.
The relevant test certificates must be observed when planning and carrying out work.


Tools / Cleaning



Broad and narrow brushes, block brush, lambskin roller, spraying equipment

Clean tools, equipment and any splashed material immediately with water while still fresh.
Ensure that any residue from cleaning is disposed of correctly.

Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Personal protective equipment

Respiratory protection with a particle filter P2 must be worn during spraying, together with protective goggles. Wear suitable protective gloves and clothing.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.