

Headset Specifications									
Type	Headset Name	S.H.I.S.	Headtube Opening	Headtube I.D.	Fork Steerer Tube	Fork Crown Seat O.D.	Stack Height ¹	Min. Ream Depth	Convertability ²
Internal	I1	ZS44/28.6 ZS44/30	Upper	44.00 mm (+0.00 -0.05)	1-1/8"	30.1 mm	8.2 mm	9.5 mm	
			Lower	44.00 mm (+0.00 -0.05)	1-1/8"		4.2 mm	9.5 mm	
	I2	ZS44/28.6 ZS56/40	Upper	44.00 mm (+0.00 -0.05)	1-1/8"	39.8 mm	8.2 mm	9.5 mm	
			Lower	55.95 mm (+0.00 -0.05)	1.5"		5.6 mm	11.0 mm	✓
	I4	ZS49/28.6 ZS49/30	Upper	49.61 mm (+0.00 -0.04)	1-1/8"	30.1 mm	8.0 mm	16.0 mm	
			Lower	49.61 mm (+0.00 -0.04)	1-1/8"		4.0 mm	16.0 mm	
Internal External	I3	ZS44/28.6 EC49/40	Upper	44.00 mm (+0.00 -0.05)	1-1/8"	39.8 mm	8.2 mm	9.5 mm	
			Lower	49.61 mm (+0.00 -0.04)	1.5"		14.2 mm	21.00mm	✓
	I5	ZS49/28.6 EC49/40	Upper	49.61 mm (+0.00 -0.04)	1-1/8"	39.8 mm	8.0 mm	16.0 mm	
			Lower	49.61 mm (+0.00 -0.04)	1.5"		14.2 mm	21.00mm	✓
	I7	ZS44/28.6 EC44/40	Upper	44.00 mm (+0.00 -0.05)	1-1/8"	39.8 mm	8.2 mm	9.5 mm	
			Lower	44.00 mm (+0.00 -0.05)	1.5"		14.0 mm	9.5 mm	✓
	I8	ZS44/28.6 EC44/33	Upper	44.00 mm (+0.00 -0.05)	1-1/8"	33.1 mm	8.2 mm	9.5 mm	
			Lower	44.00 mm (+0.00 -0.05)	1-1/4"		14.0 mm	9.5 mm	✓ ³
External	NoThreadSet™ Tapered 34/44 1.5"	EC34/28.6 EC44/40	Upper	33.95 mm (+0.00 -0.05)	1-1/8"	39.8 mm	17.7 mm	10.67mm	
			Lower	44.00 mm (+0.00 -0.05)	1.5"		14.0 mm	9.5 mm	✓ ³
	NoThreadSet™ Tapered 34/44 1-1/4"	EC34/28.6 EC44/33	Upper	33.95 mm (+0.00 -0.05)	1-1/8"	33.1 mm	17.7 mm	10.67mm	
			Lower	44.00 mm (+0.00 -0.05)	1-1/4"		14.0 mm	9.5 mm	✓ ³
	NoThreadSet™ Tapered 34/49	EC34/28.6 EC49/40	Upper	33.95 mm (+0.00 -0.05)	1-1/8"	39.8 mm	17.7 mm	10.67mm	
			Lower	49.61 mm (+0.00 -0.04)	1.5"		14.2 mm	21.00mm	✓ ³
	1.5 1-1/8" Devo	EC49/28.6 EC49/30	Upper	49.61 mm (+0.00 -0.04)	1-1/8"	30.1 mm	18.1 mm	21.00mm	✓
			Lower	49.61 mm (+0.00 -0.04)	1-1/8"		14.2 mm	21.00mm	✓
	1.5" NoThreadSet™	EC49/38.1 EC49/40	Upper	49.61 mm (+0.00 -0.04)	1.5"	39.8 mm	18.1 mm	21.00mm	✓
			Lower	49.61 mm (+0.00 -0.04)	1.5"		14.2 mm	21.00mm	✓
Stem Cap Bolt Torque = 1.7Nm (15 in.lbs)									
¹ upper stack height = upper cup + bearing cap. lower stack height = lower cup + baseplate									
² convertible to fit a 1-1/8" or 1.5" steerer tube, depending on baseplate and/or bearing cap									
³ convertible to fit a 1-1/8" or 1-1/4" tapered steerer tube, depending on baseplate									