Tesla Charger **Extension Cord**

User Manual



K LECTRON

About the Product

This extension cord adds an extra 20 feet to your Level 1 or Level 2 Tesla charger.

In the Box



1 x Tesla charger extension cord

Safety Information


- This extension cord has a maximum output of 48A
- · Before connecting to the charger, make sure the output of the charger does not exceed 48A.
- After connecting to the charger, wait 30 seconds before plugging into your Tesla.

Compatibility

- Tesla High Power Wall Connector
- Tesla Destination Charger Gen 1, 2, 3
- Tesla Mobile Connector

Page 2

Introduction to Parts



000


I. Tesla charger adapter 2. Tesla charging handle



Warnings

- Read this manual before using the Tesla Charger Extension Cord. Failure to follow the instructions or warnings in this document can result in fire, electrical shock. or serious injury.
- Do not attempt to open, disassemble, repair, tamper with, or modify the device.
- Keep away from water.
- · Keep away from flames, heaters, and other Page 3 heat sources.

How to Use



1. Plug the Tesla Charger into the extension cord. Wait at least 30s before plugging the extension cord into your Tesla vehicle.



2. Plug the extension cord into your Tesla charge port.

Note: If you are using a Tesla Destination Charger or a Tesla Wall Connector and see a red light blinking on the charger, immediately adjust the charger current to 48A or below (set the rotary switch to position 1-8).

Page 4

Is the extension cord weatherproof?

The extension cord is IP54-rated and weatherproof. However, for best performance, it is recommended to not let it get wet.

How fast can this fully charge my Tesla?

The maximum power output is 11.5kW (48A, 240V). The exact charging speed depends on different factors, such as: using a portable Tesla charger, different Tesla charging stations, different Tesla car models, etc.

Can you leave the extension cord connected to the Tesla Wall Charger?

It is recommended to disconnect the extension cord from the Tesla Wall Charger after each use

Get More Support

Scan the OR code below or email us at: contact@ev-lectron.com



Max 250V AC Voltage: Current: Max 48A -22°F to +122°F Operating temperature: Charging port: Tesla US Tesla US Connector port: 13.5 lbs Weight: 20 ft Lenath:



Tesla Charger is not included. Lectron is not affiliated with Tesla Inc. Lectron is a trademark of Dropcases Ltd. contact@ev-lectron.com Tesla Charger is a trademark of Tesla Inc.

For more information, visit: www.ev-lectron.com or contact us at Made in China

Page 5

100mm