



MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

1-1. Product name:	<input type="text" value="Forabeli Elite Eyelash Extension Glue"/>		
1-2. Synonym(s) :	<input type="text" value="None"/>	1-3. Product Code :	<input type="text" value="None"/>
1-4. General Use :	<input type="text" value="Adhesives"/>		
1-5. Product Description :	<input type="text" value="Powerful instant glue on cyanoacrylate."/>		
1-6. MSDS Number :	<input type="text" value="(E) CA-4-01"/>		
1-5. Company Name :	<input type="text" value="Forabeli Beauty Ltd."/>		

2. COMPOSITION / INFORMATION ON INGREDIENTS

--

Ingredients	Wt%	CAS Registry No	Chemical Formula
Ethyl cyanoacrylate	90	21982-43-4	CH ₂ =C(CN)-COOCH ₂ CH ₂ OCH ₂ CH ₃
PMMA	4.9	9011-14-7	
Hydroquinone	0.1	123-31-9	
Carbon black	5	1333-86-4	

3. HAZARDS IDENTIFICATION

3-1. EMERGENCY OVERVIEW :

Vapor is irritating to eyes, skin and mucous membranes and respiratory tract.

3-2. POTENTIAL HEALTH EFFECTS :

May cause sensitization by inhalation. Narcotic effects, headache, dizziness, vomiting.

3-3. Skin

dryness

3-4. Eye

irritation

3-5. Potential Environmental Effects :

Not available.

3-6. Signs And Symptoms Of Exposure :

Vapor is irritating to eyes and mucous membranes above TLV.
Prolonged and repeated overexposure to vapors may produce symptoms of non-allergic asthma in sensitive individuals.

3-7. EXISTING CONDITIONS AGGRAVATED BY EXPOSURE :

Unknown

3-8. TARGET ORGAN AND OTHER HEALTH EFFECTS :

*Literature Referenced

3-9. Ingredients

Ethylcyanoacrylate ALG IRR RES
Carcinogen NTP IARC OSHA

*

N/A Not applicable IRR Irritant
ALG AllergenRES Respiratory

4. FIRST AID MEASURES

4-1. INGESTION :

Ingestion is not likely. See supplemental page for emergency procedures.

4-2. INHALATION :

Evacuate from further exposure. If unconsciousness occurs, seek immediate medical assistance and call a physician. If the breath has stopped, have artificial respiration. If breathing difficulty occurs, have oxygen inhalation.

4-3. Skin Contact :

Remove contaminated clothing. Wash contact areas with soap and much water.

4-4. Eye contact :

Flush thoroughly with fresh water for at least 15 min. Get medical assistance immediately

5. FIRE FIGHTING MEASURES

5-1. FLASH POINT :

Above 95°C

5-2. Method :

Cleveland open cup. (Recommended)

5-2. Extinguishing agents :

Carbon dioxide, form ,dry chemical

5-3. Explosive Limits :	<input type="text" value="(%by volume in air) Lower : Not available"/> <input type="text" value="(%by volume in air) Upper : Not available"/>
5-4.Special firefighting procedures :	<input type="text" value="Not available"/>
5-5.Hazardous products formed by fire or thermal decomposition :	<input type="text" value="Irritating organic fragments."/>

6. ACCIDENTAL RELEASE MEASURES

Evacuate non essential personnel.

6-1. Shut off all sources of ignition :

***Ventilate area after material pick up is completed.**

6-2. For small spills :

6-3. For large spills :

7. HANDLING AND STORAGE

7-1. Handling :

Install emergency showers and eyewash facility in working area.

7-2. Storage :

Keep away from all possible sources of ignition.
Store in a cool, dry, well ventilated location.
Keep the container tightly closed.
Keep away from combustible materials, heat, steam pipe or sunlight.
Keep away from oxidizing materials.

7-3. Other Precautions :

Wash hands, face and gargle after work.
Practice good personal hygiene after using this material, especially before eating, drinking, smoking or using the restroom.
Keep out of reach of children. (S2)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8-1. Respiratory protection (Specify type) :

Chemical cartridge respirator with organic vapor.
Ventilation Local exhausts Should be used to control vapors in the work area.
Mechanical (General) Should use a breathing mask.

8-2. Protective gloves :

Polyethylene gloves. No rubber.

8-3. Eye protection :

Safety glasses, face shield.

8-4. Skin protection :

Other protective clothing or equipment impervious clothing, apron and boots. Barrier creams, etc.

9. PHYSICAL AND CHEMICAL PROPERTIES

9-1. Appearance :	Black liquid
9-2. Odor :	Odorless, irritating.
9-3. Boiling point :	Above 190 °C
9-4. Melting point :	N/A
9-5. Specific gravity (H2O =1) :	0.9~1.1
9-6. Vapor pressure (at25°C) :	1Pa
9-7. Vapor density (Air =1) :	4.9
9-8. Evaporation rate (Butyl acetate =1) :	N/A
9-9. Solubility in water :	Insoluble(polymerized by water)

10. STABILITY AND REACTIVITY

10-1. Condition to avoid :	High humidity, high temperature or direct sunlight.
10-2. Stability :	Stable (cool and dry area.).
10-3. Materials to avoid :	Polymerized by contact with water, alcohols, amines, alkalies.

10-4. Harardous decomposition or byproducts :	CO ₂ , oxides and nitrogen and unknown hydrocarbons.
------------------------------------------------------	-----------------------------------------------------------------

11. TOXICOLOGICAL INFORMATION

11-1. Toxicity :	Skin contact may cause burns. Bond skin rapidly and strongly. Skin and eye irritant.
11-2. Oral LD50 :	6760mg /kg in rat. (Acute) (Pro forma amount)allied substance
11-3 Routes of entry :	Inhalation (Yes), Skin (Yes), Ingestion (Yes)
11-4. Carcinogen etc :	See Section 3

12. ECOLOGICAL INFORMATION

Not data available

13. DISPOSAL INFORMATION

13-1. Waste disposal method :	<p>Don't pour drain. Follow domestic and local environmental regulations. Precautions to be taken in handling and storing. Avoid unnecessary exposure to air and moisture.Don't store above 25°C and in direct sunlight, Keep container lids tightly closed.</p>
13-2. Other Precautions :	<p>Avoid contact with skin and eyes. Protect eyes, skin and clothing from contact with liquid product. Wear recommended equipment.</p>

14. TRANSPORT INFORMATION

U.S.Department of Transportation Ground Transport (49 CFR 172)

14-1. Proper shipping name :

Unrestricted (Not more than 450 liters.)
Combustible liquids n.o.s.(Cyanoacrylate ester) (More than 450 liters)

14-2. Hazard class or division :

Unrestricted (Not more than 450 liters.)
Combustible liquids. (More than 450 liters)

14-3. Identification number :

None (Not more than 450 liters.)
NA1993 (More than 450 liters)

14-4. Marine pollutant :

None.

14-5. International Air Transportation (ICA/IATA)

14-6. Proper shipping name :

Unrestricted.

14-7. Class or division :

Unrestricted.

14-8. UN or ID number :

None.

14-9. Water Transportation (IMO/IMDG)

15. REGULATORY INFORMATION

15-1. CA Proposition 65 :

No California proposition 65 chemicals are known to be present.



16. OTHER INFORMATION

16-1. Estimated NFPA Code :	*NFPA is a registered trademark of the National Fire Protection Assn.
16-2. Health Hazard :	2
16-3. Fire Hazard :	2
16-4. Reactivity Hazard :	1
16-5. Specific Hazard :	Does not apply
16-6. Estimated HMIS Code :	*HMIS is a registered trademark of the National Paint and Coatings Assn.
16-7. Health Hazard :	2
16-8. Flammability Hazard :	2

NOTE

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Forabeli Beauty Ltd.. It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Forabeli Beauty Ltd. assumes no responsibility for use or reliance upon this information.