

6MM (1/4")

Natural Cork Underlayment Roll



200 Sq. Ft Per Roll | 48" Wide X 50' Long

For ceramic tile, stone, marble, glued wood flooring and floating floor systems

Features & Benefits

- Reduces sound transmission from both the surface of a floor as well as through the floor to living spaces below
- Acts as a crack isolation membrane that resists transfer of stress cracks from subfloor through to flooring surfaces
- Reduces thermal transmission, increasing the effectiveness of floor heating systems
- Easy to install in both glue-down and loosely configurations
- Acoustical sound control under ceramic tile and stone for less sound transfer throughout the room
- Green product constructed of natural cork, a renewable resource
- For use with on and above grade floors only

Our Natural Cork products may contribute towards satisfying credits under the LEED® Green Building Program in the following areas:

- MR 4.1 - 5% Recycled Content of total building materials (post consumer + ½ of post industrial)
- MR 4.2 - 10% Recycled Content of total building materials (post consumer + ½ of post industrial)
- MR 6 - Specifying rapidly renewable building materials for 5% of total building materials.
- EQ 4.1 - Low Emitting Materials Adhesives & Sealants (Adhesives Specified meet SCAQMD Rule 1168)

	ACOUSTICS PERFORMANCE	IIC	STC	Δ
Quality: 1 Roll	With 6" Cement Slab	51	52	22
Coverage: 200 Ft² (48" Wide X 50' Long)	With 6" Cement Slab & Suspended Ceiling	61	60	