

NAME

# Dyckman Street

SKU

AANYDS160

<b>SPECIES</b>	White Oak (European)	<b>THICKNESS</b>	20mm (3/4")
<b>CONSTRUCTION</b>	Balance Engineered	<b>WIDTH</b>	150mm (5.9")   200mm (7.9")
<b>JOINT</b>	Tongue & Groove	<b>LENGTH</b>	Random 1800mm-2200mm (6'-7')
<b>GRADE</b>	Light Character	<b>WEAR LAYER</b>	5mm
<b>CUT</b>	Plain Sawn		
<b>SURFACE</b>	Brushed		
<b>EDGES</b>	Bevel		
<b>TREATMENT</b>	Reaction Stain		
<b>FINISH</b>	Poly		
<b>GLOSS</b>	Matte		



Pattern | Plank

## Sustainability

<b>RAW MATERIAL SOURCING</b>	Lacey Act Compliant
<b>INDOOR AIR QUALITY / EMISSIONS</b>	No Added Urea-Formaldehyde (NAUF)
<b>PERFORMANCE &amp; SAFETY TESTING</b>	Janka Rating: 1360
<b>GREEN BUILDING INITIATIVE CREDITS</b>	<i>*CAN POTENTIALLY CONTRIBUTE TO</i>

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.



- LEED V4
- Living Building Challenge
- WELL
- Green Globes