



NAME

Linden Hill

SKU

AANYLH200

SPECIES	White Oak (North American)
CONSTRUCTION	Engineered
JOINT	Tongue & Groove
GRADE	Light Character
CUT	Plain Sawn
SURFACE	Lightly Brushed
EDGES	Bevel
TREATMENT	Reaction Stain
FINISH	Custom Poly
GLOSS	Matte

THICKNESS	Custom
WIDTH	Custom
LENGTH	Custom Herringbone
WEAR LAYER	Custom



Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	No Added Urea-Formaldehyde (NAUF)
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360
GREEN BUILDING INITIATIVE CREDITS	*CAN POTENTIALLY CONTRIBUTE TO
	LEED V4
, BUILDING	Living Building Challenge
FSC www.fsc.org	WELL
FSC** C132281 The mark of responsible forestry	Green Globes

Pattern | Chevron

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.