

NAME

Dupont

SKU

COC90

SPECIES	White Oak (European)	THICKNESS	20mm (3/4")
CONSTRUCTION	Engineered	WIDTH	300mm (11-13/16")
JOINT	Tongue & Groove	LENGTH	2750mm (108-1/4")
GRADE	Character	WEAR LAYER	4.5mm
CUT	Live Sawn	PACKAGING	17.75 SF/Bundle
SURFACE	Brushed	PATTERN	Plank
EDGES	Micro-Bevel		
TREATMENT	N/A		
FINISH	UV Poly		
GLOSS	Ultra Matte		



Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	TSCA Title VI / CARB Phase 2 Compliant CDPH 01350 VOC Compliant
PERFORMANCE & SAFETY TESTING	Janka Rating: XXXX Fire Rated Class II (ASTM E648)
GREEN BUILDING INITIATIVE CREDITS	<i>*CAN POTENTIALLY CONTRIBUTE TO</i> LEED V4 Living Building Challenge WELL Green Globes

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperature and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. Cracked knots are filled with putty, so small gaps between the putty and wood may appear. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor. Please also note that the color may change when exposed to light.

Only the products that are identified as such on this document are FSC certified.



FSC® C132261
Ask about our FSC Certified products
www.fsc.org

