

NAME

Ocean Grove

SKU

ESGD70

| SPECIES | White Oak (European) |
|--------------|----------------------|
| CONSTRUCTION | Engineered |
| JOINT | Tongue & Groove |
| GRADE | Character |
| СИТ | Plain Sawn |
| SURFACE | Lightly Brushed |
| EDGES | Bevel |
| TREATMENT | Reaction Stain |
| FINISH | UV Poly |
| GLOSS | Matte |
| | |

| THICKNESS | 9/16" |
|------------|-------------------------------------|
| WIDTH | 6" |
| LENGTH | Random 18"-75" (60% full length) |
| WEAR LAYER | 3mm |
| PACKAGING | 24.86 SF/Bundle |
| | |



Pattern | Plank

Sustainability

| RAW MATERIAL SOURCING | Lacey Act Compliant |
|-----------------------------------|--------------------------------|
| INDOOR AIR QUALITY / EMISSIONS | CARB Phase 2 Compliant |
| PERFORMANCE & SAFETY TESTING | Janka Rating: 1360 |
| GREEN BUILDING INITIATIVE CREDITS | *CAN POTENTIALLY CONTRIBUTE TO |
| | LEED V4 |
| SEL BUILDING | Living Building Challenge |
| FSC www.fsc.org | WELL |
| The mark of responsible forestry | Green Globes |

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.