

NAME

Lambertville

SKU

ESSO69

SPECIES	White Oak (European)	THICKNESS	9/16"
CONSTRUCTION	Engineered	WIDTH	6"
JOINT	Tongue & Groove	LENGTH	Random up to 75" (75% full length)
GRADE	Character	WEAR LAYER	3mm
CUT	Plain Sawn	PACKAGING	24.86 SF/Bundle
SURFACE	Lightly Brushed		
EDGES	Bevel		
TREATMENT	Smoked		
FINISH	UV Poly		
GLOSS	Matte		



Pattern | Plank

Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	CARB Phase 2 Compliant
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360
GREEN BUILDING INITIATIVE CREDITS	<i>*CAN POTENTIALLY CONTRIBUTE TO</i>

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.

- LEED V4
- Living Building Challenge
- WELL
- Green Globes

