

NAME

Bethalto

SKU

EWL164

SPECIES	White Oak (European)	THICKNESS	15mm (5/8")
CONSTRUCTION	Engineered	WIDTH	190mm (7-1/2")
JOINT	Tongue & Groove	LENGTH	1900mm (74-3/4") w/ starter planks
GRADE	Character	WEAR LAYER	4mm
CUT	Plain Sawn	PACKAGING	23.31 SF/Bundle
SURFACE	Brushed	PATTERN	Plank
EDGES	Micro-Bevel		
TREATMENT	Medium Smoked		
FINISH	UV Poly		
GLOSS	Matte		



Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	TSCA Title VI / CARB Phase 2 Compliant CDPH 01350 VOC Compliant
PERFORMANCE & SAFETY TESTING	Fire Rated Class II (ASTM E648)

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperature and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. Cracked knots are filled with putty, so small gaps between the putty and wood may appear. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor. Please also note that the color may change when exposed to light.

Only the products that are identified as such on this document are FSC certified.

GREEN BUILDING INITIATIVE CREDITS

**CAN POTENTIALLY CONTRIBUTE TO*



FSC® C132261
Ask about our FSC Certified products
www.fsc.org



LEED V4
Living Building Challenge
WELL
Green Globes