

## Product Cut Sheet

SKU

GN20162

## Loleta

SPECIES	White Oak (European)
CONSTRUCTION	Engineered
JOINT	Tongue & Groove
GRADE	Select
CUT	Plain Sawn
SURFACE	Smooth
EDGES	2 Side Micro-Bevel
TREATMENT	N/A
FINISH	UV Urethane
GLOSS	Ultra Matte

THICKNESS	9/16"
WIDTH	5-1/2"
LENGTH	Random 12"-84"
WEAR LAYER	3.5mm
PACKAGING	32.93 SF/Bundle



Pattern | Plank

## Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	CARB Phase 2 Compliant
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360
GREEN BUILDING INITIATIVE CREDITS	*CAN POTENTIALLY CONTRIBUTE TO
	LEED V4
A BUILDING	Living Building Challenge
FSC www.tsc.org	WELL
FSC* C132201 The mark of responsible forestry	Green Globes

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.