



NAME

## Candler

SKU

## LFO27820

SPECIES	White Oak (European)	THICKNESS	9/16
CONSTRUCTION	Engineered	WIDTH	6 - 1.
JOINT	Click System	LENGTH	70-7
GRADE	Character	WEAR LAYER	2.5m
CUT	Plain Sawn	PACKAGING	20.9
SURFACE	Brushed		
EDGES	Micro-Bevel		
TREATMENT	N/A		
FINISH	UV Lacquer		
GLOSS	Matte		

THICKNESS	9/16"
WIDTH	6 - 1/8" (155 mm)
LENGTH	70-7/8" w/ starter planks
WEAR LAYER	2.5mm
PACKAGING	20.98 SF/Bundle

Pattern | Plank

## Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	CARB Phase 2 Compliant
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360
GREEN BUILDING INITIATIVE CREDITS	*CAN POTENTIALLY CONTRIBUTE TO
	LEED V4
, BUILDING	Living Building Challenge
FSC www.fsc.org Fsc**C132281  The mark of responsible forestry	WELL
	Green Globes

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient tem-perature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will con-tain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or pho-tograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.