

NAME

Westfork

LFO37820

SPECIES	White Oak (European)
CONSTRUCTION	Engineered
JOINT	Click System
GRADE	Character
CUT	Plain Sawn
SURFACE	Brushed
EDGES	4-Side Micro-Bevel
TREATMENT	N/A
FINISH	UV Lacquer
GLOSS	Matte

THICKNESS	9/16"
WIDTH	6 - 1/8" (155 mm)
LENGTH	70-7/8" w/ starter planks
WEAR LAYER	2.5mm
PACKAGING	20.98 SF/Bundle



Pattern | Plank

Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	CDPH 1350 Compliant CARB Phase 2 Compliant
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360
GREEN BUILDING INITIATIVE CREDITS	*CAN POTENTIALLY CONTRIBUTE TO
	LEED V4
, BUILDING	Living Building Challenge
FSC www.fsc.org	WELL
The mark of reponsible forestry	Green Globes

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient tem-perature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, yearround.

Wood is a product of nature and, as such, will con-tain variations in color, grain, and character from plank to plank.
Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor

Only the products that are identified as such on this document are FSC certified.