

NAME

Comer

SKU

LFO66820

SPECIES	White Oak (European)	THICKNESS	9/16"
CONSTRUCTION	Engineered	WIDTH	8 - 1/8" (207mm)
JOINT	Click System	LENGTH	86-5/8" w/ starter planks
GRADE	Character	WEAR LAYER	3.2mm
CUT	Plain Sawn	PACKAGING	34.22 SF/Bundle
SURFACE	Brushed	PATTERN	Plank
EDGES	Micro-Bevel		
TREATMENT	N/A		
FINISH	UV Lacquer		
GLOSS	Matte		



Pattern | Plank

Sustainability

RAW MATERIAL SOURCING

Lacey Act Compliant
EPD Available

INDOOR AIR QUALITY / EMISSIONS

TSCA Title VI / CARB Phase 2 Compliant
FloorScore Certified
CDPH 01350 VOC Compliant

PERFORMANCE & SAFETY TESTING

Janka Rating: 1360
Fire Rated Class II (ASTM E648)

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperature and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. Cracked knots are filled with putty, so small gaps between the putty and wood may appear. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor. Please also note that the color may change when exposed to light.

Only the products that are identified as such on this document are FSC certified.

GREEN BUILDING INITIATIVE CREDITS

**CAN POTENTIALLY CONTRIBUTE TO*



The mark of responsible forestry



LEED V4
Living Building Challenge
WELL
Green Globes