

NAME

Kellogg

SKU

LFO67820

| | | | |
|---------------------|----------------------|-------------------|---------------------------|
| SPECIES | White Oak (European) | THICKNESS | 9/16" |
| CONSTRUCTION | Engineered | WIDTH | 6 - 1/8" (155 mm) |
| JOINT | Click System | LENGTH | 70-7/8" w/ starter planks |
| GRADE | Character | WEAR LAYER | 2.5mm |
| CUT | Plain Sawn | PACKAGING | 20.98 SF/Bundle |
| SURFACE | Brush | | |
| EDGES | Micro-Bevel | | |
| TREATMENT | N/A | | |
| FINISH | UV Lacquer | | |
| GLOSS | Matte | | |



Pattern | Plank

Sustainability

| | |
|--|--|
| RAW MATERIAL SOURCING | Lacey Act Compliant |
| INDOOR AIR QUALITY / EMISSIONS | CARB Phase 2 Compliant |
| PERFORMANCE & SAFETY TESTING | Janka Rating: 1360 |
| GREEN BUILDING INITIATIVE CREDITS | <p><i>*CAN POTENTIALLY CONTRIBUTE TO</i></p> <p>LEED V4</p> <p>Living Building Challenge</p> <p>WELL</p> <p>Green Globes</p> |

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperature and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.

