

NAME
Terrell

SKU
LFO93520

SPECIES	White Oak (European)	THICKNESS	9/16"
CONSTRUCTION	Engineered	WIDTH	7- 1/6" (180 mm)
JOINT	Click System	LENGTH	86-5/8" w/ starter planks
GRADE	Light Character	WEAR LAYER	2.5mm
CUT	Plain Sawn	PACKAGING	29.81 SF/Bundle
SURFACE	Brushed	PATTERN	Plank
EDGES	4-Side bevel		
TREATMENT	N/A		
FINISH	UV Lacquer		
GLOSS	Matte		



Sustainability

RAW MATERIAL SOURCING

Lacey Act Compliant
EPD Available

INDOOR AIR QUALITY / EMISSIONS

TSCA Title VI / CARB Phase 2 Compliant
CDPH 01350 VOC Compliant

PERFORMANCE & SAFETY TESTING

Janka Rating: 1360
Fire Rated Class II (ASTM E648)

GREEN BUILDING INITIATIVE CREDITS

**CAN POTENTIALLY CONTRIBUTE TO*



LEED V4
Living Building Challenge
WELL
Green Globes

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperature and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. Cracked knots are filled with putty, so small gaps between the putty and wood may appear. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor. Please also note that the color may change when exposed to light.

Only the products that are identified as such on this document are FSC certified.