

NAME

Design

SKU

MRF08

SPECIES	White Oak (European)	THICKNESS	12.5mm (1/2")
CONSTRUCTION	2-Layer Engineered	WIDTH	140mm (5-1/2")
JOINT	Tongue & Groove	LENGTH	Random 400mm - 2200mm (16"-86")
GRADE	Light Character	WEAR LAYER	2.8mm
CUT	Live Sawn	PATTERN	Plank
SURFACE	Brushed	RADIANT HEAT	Yes
EDGES	Micro-Bevel	INSTALLATION	Glue or Nail Above, On, or Below Grade
FINISH	UV-Cured Varnish	PRICING	\$9.00/SF
GLOSS	Ultra Matte		



Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	CARB Phase 2 Compliant
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.

Wood Grade Options




SELECT

Sound knots up to 10mm in diameter
Black knots up to 3mm in diameter
Slight color variations



LIGHT CHARACTER

Sound knots 3cm in diameter
Black knots 2cm in diameter
Color variation allowed
No sapwood



RUSTIC

Big knots and cracks (5-7cm)
Color variation allowed
Occasional sapwood