

NAME

# Wonder

SKU

MRF36

<b>SPECIES</b>	White Oak (European)	<b>THICKNESS</b>	Custom Options Available
<b>CONSTRUCTION</b>	2-Layer Engineered Solid Sawn Hardwood Top layer Baltic Birch Hardwood Plywood Core Layer (Exterior Grade)	<b>WIDTH</b>	Custom Options Available
<b>JOINT</b>	4-Side Tongue & Groove	<b>LENGTH</b>	Fixed or Random (Up to 2200mm or 7.2') 100% or 80% full length boards available
<b>GRADE</b>	Select / Light Character / Rustic (See Below)	<b>WEAR LAYER</b>	Custom Options Available
<b>CUT</b>	Live Sawn Custom Options Available	<b>PATTERN</b>	Plank / Parquet Custom Options Available
<b>ORIGIN</b>	Croatia	<b>RADIANT HEAT</b>	Yes
<b>SURFACE</b>	Brushed Custom Options Available	<b>INSTALLATION</b>	Glue or Nail Above, On, or Below Grade
<b>EDGES</b>	Micro-Bevel	<b>PRICING</b>	\$3.00 - \$6.00 per SF Volume Pricing Available for Full Container Orders  <i>Actual prices may vary based on specs and order size.</i>
<b>FINISH</b>	UV-Cured Oil Custom Options Available		
<b>GLOSS</b>	Matte Custom Options Available		



## Sustainability

<b>RAW MATERIAL SOURCING</b>	Lacey Act Compliant
<b>INDOOR AIR QUALITY / EMISSIONS</b>	CARB Phase 2 Compliant
<b>PERFORMANCE &amp; SAFETY TESTING</b>	Janka Rating: 1360

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.

## Wood Grade Options




### SELECT

Sound knots up to 10mm in diameter  
Black knots up to 3mm in diameter  
Slight color variations



### LIGHT CHARACTER

Sound knots 3cm in diameter  
Black knots 2cm in diameter  
Color variation allowed  
No sapwood



### RUSTIC

Big knots and cracks (5-7cm)  
Color variation allowed  
Occasional sapwood