

Product Cut Sheet

Placenza

S K U

YPAC325

_	SPECIES	White Oak (European)	THI
	CONSTRUCTION	Engineered Balanced 3-Layer	WI
_	JOINT	Tongue & Groove	LEN
	GRADE	Light Character	WE
-	СИТ	Live Sawn	
	SURFACE	Brushed	
	EDGES	Micro-Bevel	
	TREATMENT	N/A	
	FINISH	Varnish	
	GLOSS	Matte	

THICKNESS	15mm (5/8″)
WIDTH	165mm (6-1/2")
LENGTH	1200-2400mm (4'-8')
WEAR LAYER	5mm



Pattern | Plank

Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	CARB Phase 2 Compliant
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360
GREEN BUILDING INITIATIVE CREDITS	*CAN POTENTIALLY CONTRIBUTE TO
	LEED V4
FSC www.fsc.org	Living Building Challenge
	WELL
FSC* C132261 The mark of responsible forestry	Green Globes

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.