

## Product Cut Sheet

SKU

**YPAC334** 

### NAME

# Trapani

SPECIES	White Oak (European)	THICKNESS	15
CONSTRUCTION	Engineered Balanced 3-Layer	WIDTH	16
JOINT	Tongue & Groove	LENGTH	12
GRADE	Select	WEAR LAYER	5n
CUT	Live Sawn		
SURFACE	Brushed	-	
EDGES	Micro-Bevel		
TREATMENT	N/A	-	
FINISH	Varnish		
GLOSS	Matte		

HICKNESS	15mm (5/8")	and the second se
IDTH	165mm (6-1/2″)	
NGTH	1200-2400mm (4'-8')	
EAR LAYER	5mm	
	þ	
	1	

Pattern | Plank

## Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	CARB Phase 2 Compliant
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360
GREEN BUILDING INITIATIVE CREDITS	*CAN POTENTIALLY CONTRIBUTE TO
	LEED V4
AND	Living Building Challenge
FSC www.fsc.org	WELL
FSC° (13226) The mark of responsible foreitry	Green Globes

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.