

Medway

SKU

QOUS61

SPECIES	White Oak (European)
CONSTRUCTION	Engineered
ТИІОГ	Tongue & Groove
GRADE	Character
СИТ	Live Sawn
SURFACE	Brushed
EDGES	Bevel
TREATMENT	Lightly Fumed
FINISH	UV Acrylic Urethane
GLOSS	Matte

THICKNESS	1/2"
WIDTH	7"
LENGTH	Random 24"-71"
WEAR LAYER	3mm
PACKAGING	20.92 SF/Bundle



Pattern | Plank

Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	CARB Phase 2 Compliant
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360
GREEN BUILDING INITIATIVE CREDITS	*CAN POTENTIALLY CONTRIBUTE TO
	LEED V4
LES OULDING	Living Building Challenge
FSC www.fsc.org	WELL
The mark of responsible forestry	Green Globes

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.