

Product Cut Sheet

Madrid

White Oak (American)

Engineered

Tongue & Groove

Select & Better

Plain Sawn

Smooth

Bevel

N/A

UV Poly

Matte

THICKNESS

WIDTH

LENGTH

WEAR LAYER

Custom

Custom

Custom

Custom

SPECIES

JOINT

GRADE

SURFACE

TREATMENT

EDGES

FINISH

GLOSS

сит

CONSTRUCTION

RS1147T2-C

SKU



Pattern | Plank

Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant
INDOOR AIR QUALITY / EMISSIONS	CARB Phase 2 Compliant
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360
GREEN BUILDING INITIATIVE CREDITS	*CAN POTENTIALLY CONTRIBUTE TO
	LEED V4
FSC www.fsc.org fsc* c1323ft The mark of responsible forestry	Living Building Challenge
	WELL
	Green Globes

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.