

Product Cut Sheet

Celina UM

SKU

Custom

Custom

Custom

Custom

RS1782T2F-CRQ

	SPECIES	White Oak (North American)	THICKNESS
	CONSTRUCTION	Enginered	WIDTH
	JOINT	Tongue & Groove	LENGTH
	GRADE	Select	WEAR LAYER
_	CUT	Rift & Quarter	
	SURFACE	Smooth	
	EDGES	Micro-Bevel	
_	TREATMENT	N/A	
	FINISH	UV Poly	
	GLOSS	Ultra Matte	



Pattern | Plank

Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant	
INDOOR AIR QUALITY / EMISSIONS	TSCA Title VI / CARB Phase 2 Compliant	
	CDPH 01350 VOC Compliant	
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360	
GREEN BUILDING INITIATIVE CREDITS	*CAN POTENTIALLY CONTRIBUTE TO	
	LEED V4	
	Living Building Challenge	
FSC www.tiszg	WELL	
www.fs.cong PBCC (132281 The ensk of responsible foreign	Green Globes	

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.