

## Product Cut Sheet

## Pataskala

SPECIES	White Oak (European)	THICKNESS
CONSTRUCTION	Engineered	WIDTH
JOINT	Tongue & Groove	LENGTH
GRADE	Character	WEAR LAYER
CUT	Plain Sawn	
SURFACE	Brushed	
EDGES	Bevel	
TREATMENT	N/A	
FINISH	UV Poly	
GLOSS	Matte	

## S K U

RS981T2-CC



Pattern | Plank

## Sustainability

RAW MATERIAL SOURCING	Lacey Act Compliant	
INDOOR AIR QUALITY / EMISSIONS	CARB Phase 2 Compliant	
PERFORMANCE & SAFETY TESTING	Janka Rating: 1360	
GREEN BUILDING INITIATIVE CREDITS	*CAN POTENTIALLY CONTRIBUTE TO	
	LEED V4	
ALL DULL DIRG	Living Building Challenge	
FSC www.tccorg	WELL	
F3C* 0132281 The next of responsible foreity	Green Globes	

According to the National Wood Flooring Association (NWFA), wood is hygroscopic in nature – meaning it will expand and contract as it gains or loses moisture due to changes in the ambient temperature and relative humidity. Wood flooring will perform best when the interior environment is controlled to maintain a consistent and adequate range in temperate and relative humidity, year-round.

Wood is a product of nature and, as such, will contain variations in color, grain, and character from plank to plank. Variations can include knots, cracks, sapwood, mineral streaks, burls, and other distinct features, none of which constitute a defect in the material. No single sample, display board, or photograph can fully depict the entire range of visual characteristics in a hardwood floor.

Only the products that are identified as such on this document are FSC certified.

Custom

Custom

Custom

Custom