



www.torq-engineering.com

# INSTALLATION INSTRUCTION

---

## Part # RAV-CARGO

### Notice to Dealer / Consumer

**Important! Read all instructions before attempting any work on the vehicle.**

**Disclaimer Notice:** Installing this suspension system on any vehicle implies that you are in agreement with the following term and conditions with respect to that vehicle, the vehicle owner, and any or all occupants of said vehicle at any time:

- Torq Engineering is not responsible, and cannot be held responsible for any conditions of said vehicle including, but not limited to the following: 1) Any and all adverse behavior, premature failure, or breakage caused by oversized tires and wheels, improper installation, failure to follow instructions, or any general negligence caused by installer or owner of said vehicle. 2) Any breakage or premature failure caused by racing or driver negligence. 3) Any incident determined to be caused by an increase height in said vehicle's center of gravity. 4) Any incident determined to be caused by improper installation. 5) Any incident determined to be caused by a failure of materials.
- Torq Engineering is to be held harmless by the installer of this suspension component, owner of said vehicle, and any parties related directly or indirectly to said vehicle or owner of said vehicle. Torq Engineering is to be held harmless by all parties mentioned during the course of any and all circumstances or incidence resulting from the installation of this suspension component.
- It is not the intention of Torq Engineering that said vehicle be modified for use on public highways sanctioned by the Department of Transportation, or any state or local governing body. Vehicle owner accepts sole responsibility for ensuring that said vehicle is not in violation of local, state, or federal laws or vehicle code. Please check local vehicle laws and regulations before modifying your vehicle.

**By installing this kit or having this kit installed on your vehicle, you are implying that you agree to the above terms and conditions. Please do not install this system if you do not agree.**

### WARNING:

Vehicle modified for Off-road use may handle differently and vehicle may roll-over.

Vehicles modified for off-road are generally not designed to improve cornering or maneuverability on the highway, therefore it is imperative to familiarize yourself and all operators of the vehicle of the special driving characteristics of the vehicle. Failure to operate vehicle in a safe and conservative manner may cause you, your passengers and third parties to suffer serious injury or even death if control is lost and vehicle overturns.

Always wear your seatbelt and shoulder harness. Seatbelts not only help to protect occupants from injury but also keep the driver behind the wheel and in control when operating in rough terrain. Always remain on trails and observe conservation techniques while operating your vehicle.

## 2019+ TOYOTA RAV4 REAR CARGO RACK

### Bill of Materials

2	MOUNTING BRACKETS ( LH / RH )
1	CARGO RACK
4	¼-20 Rubber Well Nuts
6	¼-20 X ½ STAINLESS BUTTON HEAD CAP SCREWS.
4	¼-20 X 1-1/8 STAINLESS BUTTON HEAD CAP SCREWS.

### INSTALLATION NOTES:

- Inspect the contents of the kit and read the entire instructions before proceeding.
  - We recommend this installation be performed by a qualified technician
  - Torque all hardware to factory specifications
  - We recommend using red Loctite on all bolts
1. Assemble the Cargo Rack. Bolt on the side mounting brackets using the ¼-20 x ½" Button Head screws. Cargo rack sits on top of the mounting brackets.



2. Test fit and align the cargo rack into the vehicle, Adjust as necessary.



3. Center punch or mark the mounting holes with a marker (4 holes)



4. Remove the Cargo rack. Drill small pilot hole first then use a 1/2" drill bit.



5. Install the 1/4" Rubber Well Nuts.



6. Reinstall the Cargo Rack and use the ¼-20 x 1-1/8" Button Head Screw to attach the cargo rack.

