

Digital multimeter MD 9070 Insulation / Continuity Digital Multimeter

NEW



The MD 9070 is a high accuracy insulation and continuity multimeter which may be used in a CAT IV / 600 V environment. It's dual digital display provides all needed data to the operator while it's size ensures that it can be operated single handedly. The instrument is equipped with a built-in VFD feature that makes the instrument capable of measuring true RMS values in accordance with frequency, performing PI/DAR measurements and diode test. The MD 9070 has a wide range of extra features, including data hold, memory, min / max, differential, auto power off, auto-ranging, frequency filter, lock feature, reset, relative function and more.

MEASURING FUNCTIONS

- TRMS measurement;
- Insulation resistance measurement;
- Earth continuity measurement;
- Resistance measurement;
- Diode test;
- Mains supply frequency measurement.

KEY FEATURES

- **TRMS** for accurate readings of sinusoidal and non-sinusoidal signals.
- **PI/DAR** feature.
- **VFD** feature makes the instrument capable of measuring the true values in accordance with frequency.

• Auto-ranging.

- **Relative zero** for comparing the difference between signals or removing background noise.
- **MAX/MIN/AVG** function.
- **Data Hold** feature freezes the display for later view.
- **CAT IV / 600 V** and CAT III / 1000 V overvoltage protections.
- **Backlight** for working in dark conditions.

APPLICATION

- Insulation and earth continuity tester for preventive maintenance;
- High level industrial testing;
- High level electronic fault finding;
- Field servicing;
- Heavy duty electrical testing.

STANDARDS

- CAN/CSA-C22.2 No. 61010-1-12 Ed. 3.0
- EN61326-1:2006
- EN55022
- EN61000-3-2
- EN61000-3-3
- EN61000-4-2
- EN61000-4-3
- EN61000-4-4
- EN61000-4-5
- EN61000-4-6
- EN61000-4-8
- EN61000-4-11
- IEC/UL/EN61010-1 Ed. 3.0
- IEC/EN61010-2-030 Ed. 1.0
- IEC/EN61010-2-033 Ed. 1.0
- IEC/UL/EN61010-031 Ed. 1.1
- IEC/EN61557-1
- IEC/EN61557-2
- IEC/EN61557-4

Directives

- 2004/108/EC EMC
- 2006/95/EC LVD

TECHNICAL SPECIFICATION

Function	Range	Accuracy
TRMS AC Voltage (50 Hz ~ 5 kHz)	6.000 V ... 1000 V	From $\pm(1.0\% \text{ of reading} + 3 \text{ digits})$ to $\pm(4.0\% \text{ of reading} + 5 \text{ digits})$
VFD AC Voltage (10 Hz ~ 440 Hz)	600.0 V	From $\pm(4.0\% \text{ of reading} + 5 \text{ digits})$ to $\pm(7.0\% \text{ of reading} + 5 \text{ digits})$
DC Voltage	6.000 V ... 1000 V	From $\pm(0.2\% \text{ of reading} + 3 \text{ digits})$ to $\pm(0.3\% \text{ of reading} + 3 \text{ digits})$
Ohms	600.0 Ω ... 60.00 M Ω	From $\pm(0.9\% \text{ of reading} + 2 \text{ digits})$ to $\pm(3.0\% \text{ of reading} + 6 \text{ digits})$
Audible Continuity Tester	between 20 Ω and 200 Ω	Response time < 30 ms
Diode Tester	2.000 V	$\pm(1.5\% \text{ of reading} + 4 \text{ digits})$
Earth Continuity Test	0.015 Ω ... 2.199 Ω at $I_{test} > 200 \text{ mA}$ 0.15 Ω ... 21.99 Ω at $I_{test} > 90 \text{ mA}$	$\pm(1.5\% \text{ of reading} + 3 \text{ digits})$ $\pm(1.5\% \text{ of reading} + 3 \text{ digits})$
Hz Line Level Frequency	10 Hz ... 440 Hz; range VFD 600 V 10 Hz ... 20 kHz; range 6 V ... 1000 V	$\pm(0.02\% \text{ of reading} + 4 \text{ digits})$ $\pm(0.02\% \text{ of reading} + 4 \text{ digits})$
Insulation Resistance	3.000 M Ω ... 55.0 M Ω at 50 V 3.000 M Ω ... 110.0 M Ω at 100 V 3.000 M Ω ... 275.0 M Ω at 250 V 3.000 M Ω ... 550.0 M Ω at 500 V 3.000 M Ω ... 300.0 M Ω at 1000 V 3000 M Ω at 1000 V 25.0 G Ω at 1000 V	$\pm(1.5\% \text{ of reading} + 5 \text{ digits})$ $\pm(1.5\% \text{ of reading} + 5 \text{ digits})$ $\pm(2.0\% \text{ of reading} + 5 \text{ digits})$ $\pm(10.0\% \text{ of reading} + 5 \text{ digits})$
Sensing	AC, True RMS.	
Overload Protections	Insulation Resistance: 0.4 A / 1 KV, IR 30 kA or better Earth Continuity Test: 0.25 A / 1 KV, IR 30 kA or better. V: 1100 Vrms. mV, Ω & Others: 1000 Vrms.	
Power Supply	Four Alkaline AA batteries (IEC LR6).	
Power Consumption	4.5mA typical	
Dimension (L x W x H)	208 x 103 x 64,5 mm with holster.	
Weight	635 g with holster.	

ORDERING INFORMATION



Standard set MD 9070

- Multimeter MD 9070 with rubber holster
- Test lead with probe, 2 pcs
- Insulated crocodile clip, 2 pcs
- Insulation/Continuity test lead with probe, 1 pcs
- 1,5 V AA battery (IEC LR6), 4 pcs
- User manual

OPTIONAL ACCESSORIES

Photo	Order No.	Acc. description
	AMD 9022	Magnetic Hanging Strap

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery.
Subject to technical change without notice.



DUNCAN
INSTRUMENTS • CANADA LTD.
Electronic Measurement Solutions since 1968

www.duncaninstr.com

416-742-4448

