N-Type TOPCon 16 BB Solar PV Module

SHARK 575-700W | Dual Side Power Generation



50,000+ Happy Homes and Businesses & counting...

500+

Cities

being served currently

3500+

Resellers

pan India

15

Days

installation time

50+

Sectors

and industries served

5

Strategically located


warehouses for fast delivery time

Various Solar Applications Reducing Carbon Footprint















Get loan for your rooftop solar

@ **9.5**%`



Loan to Value Up to 80%



Lease Tenure Up to 7 years



Interest Rate 9-15%



Online Process

Technical Specifications

Model Name	SHARK 10	SHARK 20	SHARK 55	SHARK 225	SHARK 455	SHARK 455 Bifacial	SHARK 550	SHARK 550 Bifacial	SHARK 575 Bifacial
Power (Pm) in watts	10	20	55	225	455	455	550	550	575
No. of cell	36	36	36	72	144	144	144	144	144
No. of Bus Bar	2	2	9	9	9	9	10	10	16
Voltage at Maximum Power (Vmp) in Volts	19.25	19.25	21.00	21.00	42.30	42.30	42.74	42.40	43.00
Current at Maximum Power (Imp) in Amps	0.52	1.04	2.62	10.72	10.76	10.80	12.89	12.98	13.38
Open Circuit Voltage (Voc) in volts	22.50	22.50	24.50	25.00	49.50	49.45	49.60	50.20	50.50
Short Circuit Current (Isc) in Amps	0.58	1.11	2.83	11.45	11.50	11.55	13.72	13.82	14.30
Maximum system Voltage (VDC)	600	600	1000	1000	1500	1500	1500	1500	1500
Module Efficiency (%)	14%	14.20%	18%	20.4%	20.95%	21.00%	21.35%	21.40%	22.30%













