

MYLANDS

TEAK OIL FOR INTERIOR & EXTERIOR TIMBER

PRODUCT NAME/COLOUR	CODE	FINISH	VOC LEVEL
Teak Oil	09 770 8232	Satin	410g/l

PRODUCT DETAILS

Teak Oil is a blend of Tung Oil and Linseed Oil which nourishes and enhances the natural beauty of hardwoods and exotic timbers, such as Teak and Iroko.

It contains U/V filters for protection against colour change due to sunlight and is therefore suitable for both interior and exterior use.

Teak Oil is NOT suitable for exterior use on oak.

Teak Oil may be used on new or aged timber.

APPLICATION

- ◆ Always test on an off-cut of timber or an inconspicuous area of furniture to check colour and finish is as desired.
- ◆ If the timber has been previously coated, remove the old coating with either Mylands Special De-waxing solution (for wax finishes) or paint and varnish remover (for lacquer finishes).
- ◆ Clean, dry and sand the timber – ensuring all dust is removed.
- ◆ Teak Oil may be applied using a clean, white, lint-free cotton cloth or brush.
- ◆ Work the oil well into the wood, leave for up to 15 minutes before wiping off surplus. Failure to wipe off surplus will prevent penetration of subsequent coats and leave a sticky surface – if surface becomes sticky, remove stickiness with White Spirit, (09 899 9262,) and allow to dry before proceeding.
- ◆ Leave for a 24 hours and repeat the process for the remaining coats. Minimum coats recommended is three, but more may be required depending on the condition and absorbency of the substrate.
- ◆ A light rub over with 0000 grade wire wool or fine abrasive paper between coats will improve smoothness and feel of the finish. Use abrasive paper on exterior timber.

PRODUCT BENEFITS

Hard wearing satin sheen finish on hardwoods.

Ideal for protection and refurbishment of garden furniture as it replaces natural oils which are lost through weathering.

Gives a natural open grain appearance

Forms a water-resistant coating which prevents water ingress into the timber

COVERAGE

On average per litre **10-12 m²** dependant on substrate absorbency and method application.

DRYING TIME



Recoat time
24 hr (at 20°C)



Minimum 4 days
before using.

CLEANING

Use White Spirit, (09 899 9262).

Wash brushes immediately after use before the oil dries.

THINNING

Teak Oil should not normally require thinning, but if desired use White Spirit, Product code 09 899 9262.

STORAGE

Always replace the container lid, otherwise the oil could deteriorate.

Store at a temperature above 5°C.

MYLANDS

TEAK OIL (CONTINUED) FOR USE ON INTERIOR & EXTERIOR TIMBER

MAINTENANCE

Clean oiled surfaces with a damp cloth.

For more soiled surfaces a small amount of liquid detergent may be added to the water.

Old or worn oiled surfaces may be refurbished by abrading the surface and applying further coats of Teak Oil.

Exterior timber will require re-oiling at least annually – horizontal surfaces and very exposed areas may require more frequent re-coating.

HEALTH & SAFETY

Refer to Mylands Teak Oil MSDS before use

Rags used for Teak Oil should not be left rolled or screwed up as they can spontaneously combust. Either spread out to dry or put in a container with water.

SIZES AVAILABLE

