

# MYLANDS

## TUNG OIL FOR USE ON INTERIOR & EXTERIOR WOOD

PRODUCT NAME/COLOUR	CODE	FINISH	VOC LEVEL
TungOil	09 799 9150	Matt	zero g/l

### PRODUCT DETAILS

Tung Oil is an easy to apply durable coating for wood.

Pure Tung Oil is a drying oil, which means it hardens on exposure to air and consequently may be used as a coating for wood.

### APPLICATION

- ◆ Pure Tung Oil may be used on new or aged timber. Always test Pure Tung Oil on an off-cut of timber or an inconspicuous area of furniture to check colour and finish is as desired before oiling the whole article.
- ◆ If the timber has been previously coated, remove the old coating with either Mylands Special De-waxing solution (for wax finishes) or paint and varnish remover (for lacquer finishes). Clean, dry and sand the timber – ensuring all dust is removed.
- ◆ The following stains are suitable under Pure Tung Oil: Light Fast Stains, Non Fade Stains, Water Based Stains, Earth stains. Stains must be fully dry before application of the Pure Tung Oil.
- ◆ For ease of application, thin the first coat 1:1 with White Spirit (09 899 9262).
- ◆ Apply the first coat with a brush or white lint-free cotton cloth, allow to penetrate for 20 to 30 minutes and wipe off the excess with a clean lint-free cloth.
- ◆ Allow to dry for 24 hours and lightly denib with 0000 grade wire wool.
- ◆ Apply successive coats in similar manner, reducing the ratio of White Spirit each time.
- ◆ The last coat(s) should be applied unthinned. 24 hours after the final coat, wipe over again using a clean cloth to remove any oil which may have surfaced.
- ◆ A minimum of four coats of oil is recommended for porous or external surfaces. After a few days drying, the surface may be waxed to improve lustre.

### PRODUCT BENEFITS

#### Hardwearing matt finish

#### Heat, water, alcohol, food, acid resistant.

Ideal for surfaces such as kitchen and bathroom worktops, table tops and all other interior wood.

#### It resists water better than any other pure oil finish.

**Natural & non-toxic.** Can be used on toys and objects which come into contact with food, such as wooden bowls, chopping boards and worktops.

#### A good coating for exterior oak.

#### Does not darken noticeably with age.

### COVERAGE

On average per litre **10-12 m<sup>2</sup>** dependant on substrate absorbancy and method of application.

### DRYING TIME



Recoat time  
**24 hours**



**Minimum 4-7 days**  
before using (at 20°C).

### CLEANING

Use White Spirit (09 899 9262).

Wash brushes immediately after use before the oil dries.

### THINNING

Teak Oil should not normally require thinning, but if desired use White Spirit (09 899 9262).

### STORAGE

Always replace the container lid, otherwise the oil could deteriorate.

Store at a temperature above 5°C.

# MYLANDS

## TUNG OIL (CONTINUED) FOR USE ON INTERIOR & EXTERIOR WOOD

---

### MAINTENANCE

Clean oiled surfaces with a damp cloth. For more soiled surfaces a small amount of liquid detergent may be added to the water.

Old or worn oiled surfaces may be refurbished by abrading the surface and applying further coats of Pure Tung Oil as in 'Application' section.

Exterior timber will require re-oiling at least annually – horizontal surfaces and very exposed areas may require more frequent re-coating.

---

### HEALTH & SAFETY

Refer to Mylands Pure Tung Oil MSDS before use.

Pure Tung Oil is extracted from nuts and could cause an allergic reaction.

---

### SIZES AVAILABLE

