# **MYLANDS**

### OLIVE STONE WALL PRIMER

FOR INTERNAL USE

PRODUCT NAME

CODE

SHEEN LEVEL

Wall Primer

50 010 0030

6%

#### PRODUCT DETAILS

A high-quality, water-based, durable wall primer with high bio-based content, plant-based resin and a natural fillers suitable for freshly plastered walls and ceilings. The perfect complementary base to Olive Stone Emulsion, this primer seals and sets surfaces to help create the perfect finish.

#### APPLICATION

- Ensure all surfaces are clean, dry and free of contamination. The primer is supplied ready to use, if deemed necessary it can be thinned up to 10%.
- If painting over powdery or porous surfaces use stabilising solution first.
- ◆ Treat algal/fungal contaminated surfaces with dilute bleach or with a proprietary wash, then wash and clean thoroughly to remove all debris.
- Do not use in extremes of temperature. Use between 8°C (46.4°F)to 30°C (86°F).

# THINNERS

If required, the primer maybe thinned with up to 10% water.

#### HEALTH & SAFETY

Refer to Mylands MSDS before use.

#### PRODUCT BENEFITS



**Excellent adhesion properties** 



Low odour

#### COVERAGE PER COAT

Average coverage per: 1 Litre Tin  $15m^2$   $162 ft^2$ 

2.5 Litre Tin 37.5 m<sup>2</sup> 405 ft<sup>2</sup> 5 Litre Tin 75 m<sup>2</sup> 810 ft<sup>2</sup>

dependant on the porosity and texture of the substrate..

#### DRYING TIME



Touch dry in 1-2 hours.



Recoat in 4 hours.

#### CLEANING

Wash brushes/rollers immediately after use, in warm water containing a little detergent.

#### STORAGE


This product must be protected from frost. Store at temperature above  $5^{\circ}\text{C}/41^{\circ}\text{F}$ 



Use within 18 months.

+5°C/41°F

## SIZES AVAILABLE



# MYLANDS

# OLIVE STONE WALL PRIMER FOR INTERNAL USE (CONT.)

### AVAILABLE COLOURS

Our 11 shades of tinted primers have been created as the perfect base for our paints, to ensure the depth of colour is at its absolute best.

See our colour cards for our recommended pairings.

