

MYLANDS

ACRYLIC WATER STAINS FOR USE ON INTERIOR WOOD

PRODUCT NAME/COLOUR	CODE	VOC LEVEL
Wood Shades:		
Brown Mahogany	11 767 4005	55g/l
Dark Oak	11 767 4023	55g/l
Golden Oak	11 767 4031	55g/l
Jacobean Oak	11 767 4006	55g/l
Light Oak	11 767 4021	55g/l
Medium Oak	11 767 4022	55g/l
Red Mahogany	11 767 4042	55g/l
Rosewood	11 767 2290	55g/l
Walnut	11 767 4050	55g/l
Yew	11 767 4007	55g/l
Other colours:		
Black	11 767 2000	55g/l
White	11 767 2040	55g/l

PRODUCT DETAILS

This is a range of water based stains containing a small amount of acrylic binder to aid timber wetting.

The stains are based on light-fast dyes producing a comprehensive range of wood shades which have good transparency.

They are suitable for most interior use on both new and stripped timber.

They may be used on all timbers, but are more suited to soft woods.

The stains may be intermixed to give the precise shade required.

Because the stains are water based they may give some grain-raising – drying quickly will minimise this.

Acrylic Water Stains may be used under all Mylands lacquer types with the exception of Mylac flooring lacquers.

These stains will not mix with any solvent based stain or lacquer.

APPLICATION

- ◆ Timber should be evenly sanded with a minimum of 180 grit paper prior to staining to ensure the stain applies and dries without patchiness.
- ◆ It is important that clean white, lint-free cloth is used for application and wiping as colour could be leached out of coloured cloth by the stain and affect the final colour.
- ◆ Ensure equipment is stainless steel to prevent corrosion by the water in the stain.
- ◆ Acrylic Water Stains may be applied by:

Hand ragging application:

- ◆ Use a clean, soft, white lint-free cloth and apply evenly to wet the whole surface being stained before wiping off the surplus stain with a clean lint-free cloth.

Spray/wipe application:

- ◆ Spray an even wet coat to the entire surface and wipe off the surplus with a clean lint-free cloth.

Dip application:

- ◆ Dip item into the stain, then remove and allow to drain for approximately 1 minute. Finally wipe off surplus stain with a clean lint-free cloth.

MYLANDS

ACRYLIC WATER STAINS (CONTINUED) FOR USE ON INTERIOR WOOD

COLOUR MATCHING

As already mentioned, these stains may be mixed to give other colours. However if you cannot achieve the desired colour by this method, Mylands will (for a charge) match your colour for you. You will need to supply a colour pattern and some of the substrate on which the stain will be used.

STORAGE

Protect from frost – store at a temperature above 5°C.
There is no fire hazard with these products.

HEALTH & SAFETY

Refer to Mylands Acrylic Water Stain MSDS before use.

COVERAGE

On average per litre **8-10 m²** dependant on substrate porosity and method of application.

DRYING TIME



1 hour minimum at 20°C
before overcoating.

CLEANING

Clean equipment with water.

THINNING

If it is thought necessary to weaken these stains, use water.

SIZES AVAILABLE

