

MYLANDS

LIQUID FLOOR WAXES FOR USE ON FINISHED WOODEN SURFACES

PRODUCT NAME/COLOUR	CODE	VOC LEVEL
Liquid Floor Wax	16 789 8700	n/a

PRODUCT DETAILS

Mylands Liquid floor wax cleans, shines and maintains floors and other finished wooden surfaces.

Liquid Floor Wax is a clear wax designed for use on pre-sealed flooring.

The floor may be sealed with shellac, pre-catalysed, acid catalysed, polyurethane or water-based flooring sealers.

Liquid Floor Wax will also enrich and enhance the appearance of a slightly worn floor coating and maintain a good level of protection if used correctly and on a regular basis.

Mylands Liquid Floor Wax contains a slip-resistance additive, but care should be taken – particularly if the floor has water present. For that reason, Liquid Floor Wax is NOT recommended for kitchens or bathrooms.

APPLICATION

- ◆ Mylands Liquid Floor Wax should be applied to a previously sealed floor – see ‘Preparation of floor’ section above.
- ◆ Shake Liquid Floor Wax well before use to ensure it is fully homogenous.
- ◆ At low temperatures the product may be difficult to pour, so it may be beneficial to warm it slightly by immersing the container in hot water for a short period. Liquid Floor Wax may be applied by brush, roller or floor mop.
- ◆ Apply an even coat across the whole floor and allow to dry for 1 – 2 hours (depending on temperature).
- ◆ When adequately dry, the wax will have a dull sheen and may then be buffed.
- ◆ Using a polishing machine, wax brush or coarse cloth.

PREPARATION

New floor:

The surface to be finished must be clean, dry and free from any contamination. Pre-sand the timber with 100 or 120 grit paper and remove sanding dust prior to wax application.

Apply one coat of Mylands shellac, acid catalysed, polyurethane or water-based flooring sealer and allow to dry for a minimum of 2 hours.

Previously finished floors:

Ensure the surface is clean, dry and free from dust.

COVERAGE

On average per litre **8-12 m²** dependant on type and porosity of timber.

DRYING TIME



1-2 hours (wax film will have a dull sheen) before buffing.

CLEANING

Clean equipment with White Spirit (09 899 9262).

Any wax which comes into contact with other substrates, such as painted skirting boards, should be removed quickly with White Spirit.

THINNING

These products should be used as supplied and do not require thinning.

MYLANDS

LIQUID FLOOR WAXES (CONTINUED) FOR USE ON FINISHED WOODEN SURFACES

MAINTENANCE

To maintain the shine, the surface may be re-buffed without the application of more wax when necessary.

If, after repeated re-buffing, the surface no longer has an adequate shine, a further coat of Liquid Floor Wax may be applied and buffed as in 'Application' above.

Domestic floors should require re-waxing no more than three times a year.

To maintain shine on Floors which receive heavy wear, they will need the wax film renewing more frequently with more frequent re-buffing in between.

HEALTH & SAFETY

Refer to Mylands Liquid Floor Wax MSDS before use.

STORAGE

Replace container lid after use and store in a cool place.

SIZES AVAILABLE

