

## COLOUR DUOX VEO-XS MONITOR 4,3"



**Reference:** 9408

Hands-free VEO-XS monitor. Characterised by its small size and extra-flat thickness. Thanks to its OSD menu and the layout of the buttons, interaction with the user is simple and intuitive. Made of..

### DESCRIPTION

Hands-free VEO-XS monitor. Characterised by its small size and extra-flat thickness. Thanks to its OSD menu and the layout of the buttons, interaction with the user is simple and intuitive. Made of high impact ABS plastic. Texturised finish for easy cleaning and ultraviolet protection. Surface installation. VEO-XS incorporates a 4,3" (16:9) panoramic color TFT screen. Its balanced design of pure lines is distinguishing, modern and minimal. VEO-XS integrates in the ambience. When a call is received, the image appears automatically. When the conversation button is pressed a conversation with the visitor can take place. The image is de-activated automatically after 90 seconds, or when the button is pressed again. To open the door, press the button key.

**ACCESORIES  
 CONNECTOR**

9407 DUOX VEO-XS MONITOR CONNECTOR  
 Necessary to mount the monitor on the wall surface.

**REPLACEMENT**

3388 UNIVERSAL FRAME 120X240  
 Universal frame with an extra slim format, it is manufactured in a high resistant ABS plastic with a texturised finish. In replacement works, allows to cover the space left by older equipment. In addition, it keeps the wall protected from the dirt reproduced by the use of telephones and monitors. Dimensions: 120 x 240 x 10 mm.

3389 UNIVERSAL LARGE FRAME 210X240  
 Dimensions: 120 x 240 x 10 mm

### TECHNICAL SPECIFICATIONS

**GENERAL CHARACTERISTICS**

- Technology DUOX (non-polarized 2 wire full digital system)
- Audio/Video system Audio/Video Color
- Set-up (Installation) Surface mounted (connector ref. 9407)
- Desktop support -
- Handset with magnet to facilitate the hang up -
- Hands-free communication Yes
- Press-to-talk communication configurable Yes
- Induction loop included Yes (FFR09408)



Screen dimensions 4,3" (Panoramic 16:9)  
Screen resolution (H x V) 480 x 272  
Color of the product Matt white  
Number of pushbuttons 5  
Kind of pushbuttons Mechanical (silicon)  
Number of leds for lighted indications 3 (red, blue and green)

### PROGRAMMING OF THE TERMINAL ADDRESS

From the terminal From the OSD menu  
From the outdoor panel or guard unit Yes  
From the outdoor panel throughout the apartment door bell Yes

### FEATURES

Automatic picture capture when the visitor calls (PHOTOCALLER) Yes (1 photo/call, until 150 photos, 320 x 240 pixels)  
Guard unit call Yes (by means of the door release button)  
Auto-on Yes (with 3 outdoor panels)  
OSD menu Yes  
Additional function F1 Yes (Button F1 sends a negative and/or command)  
Additional function F2 Yes (it only sends command, no negative)  
Apartment door bell Yes  
Connection for additional devices (call extension, light/buzzer activator, etc.) Yes  
Doormatic (automatic door release for offices, etc.) Yes (configurable until 12h)

### ADJUSTMENTS

Date and time Yes  
Ring tones selection Yes (5)  
Call volume control Yes (8 levels by OSD menu and sliding wheel)  
Do-not-disturb mode Yes (by OSD menu)  
Audio volume control Yes (8 levels by OSD menu and sliding wheel)  
Brightness, color and contrast control Yes (by OSD menu)

### TECHNICAL FEATURES

Product dimensions (width x height x depth) mm 125 x 165 x 21  
Time to answer or open the door since the call is done 30 s.  
Conversation time 90 s.  
Conversation privacy Yes  
Voltage 18 Vdc  
Maximum consumption (mA) 370  
Standby consumption (mA) 38  
Working temperature (°C) [-5°C, +40°C]  
Humidity [0%, 90%]  
Product Weight (kg) 0,29  
Line adaptor included in the terminal Yes (default position OFF)  
Connections Bin, Bin, Bout, Bout, -, A+, F1, T

**Weight:** 0,2949 kg

**Size of product when packed:** 17,6x12,8x3,4 cm

**EAN 13:** 8424299094083

#### HEAD OFFICE

U1, 37-39 Green St,  
Banksmeadow, NSW. 2019  
p. 61 2 9700 1700  
f. 61 2 9700 1955  
sales@fermaxaus.com.au

#### QLD OFFICE

U11, 8 Fortitude Cres,  
Burleigh Heads, QLD. 4220  
p. 61 7 5520 2266  
f. 61 7 5520 4591  
qld@fermaxaus.com.au

#### VIC OFFICE

U30, 640-680 Geelong Rd,  
Brooklyn, VIC. 3012  
p. 61 3 9314 2220  
f. 61 3 9314 7772  
vic@fermaxaus.com.au

#### WA OFFICE

U2, 26 Gibberd Rd,  
Balcatta, 6914  
p. 61 8 9240 2624  
wa@fermaxaus.com.au

#### SA OFFICE

PO Box 161  
Torrensville Plaza, 5031  
m. 64 438 700 811  
sa@fermaxaus.com.au

#### NZ OFFICE

PO Box 112 110  
Penrose, 1642  
m. 64 27 566 0222  
p. 64 9 337 6229  
nz@fermaxnz.co.nz

