

PRODUCT DATA

ALKA CONCENTRATE

Grease and Oil Emulsifier

For Use in Kitchens and on Concrete and Asphalt Surfaces

ALKA CONCENTRATE has been formulated to dissolve and disperse oil and grease accumulation on concrete and asphalt surfaces. It is also extremely effective in clean up of vents, hoods, fans, stove components and meat blocks in a food processing or restaurant facility.

Excellent for use on driveways, parking lots, garage and shop floors. Used by service stations, automotive repair shops, machine shops, transit authorities, apartment complexes, etc.

DIRECTIONS

Spray or brush a diluted solution of **ALKA CONCENTRATE** on the surface to be cleaned (see below). Allow 5 to 10 minutes for the chemical to penetrate and emulsify the grease. Then agitate with a long handled, stiff bristle brush. Follow with a clear water rinse.

DILUTION RATES

Severe Accumulations: Dilute concentrate 1 to 1 with warm water.

Heavy Soil: Dilute 1 part concentrate with up to 5 parts water (26 ounces per gallon of water).

Medium Soil: Dilute 1 part concentrate with up to 10 parts water (13 ounces per gallon of water).

Light Soil: Dilute 1 part concentrate with up to 20 parts water (6.5 ounces per gallon of water).

Refer to the Material Safety Data Sheet for safety information.
FOR INDUSTRIAL and INSTITUTIONAL USE ONLY.