FLOS



by Michael Anastassiades , 2018

Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.4m

| Mounting | Pendant |
|----------------------------|--|
| Environment | Indoor |
| Weight | 0.65 Kg |
| Light sources available | 1 x FLEX STRIP LED 24W 1200lm 2700K CRI90 [i] |
| Emergency | Without |
| Voltage | 48V |
| Power | 24W |
| Battery | No |
| Supply included | No |
| Cord Length | 2400 mm |
| Materials | Aluminum |
| Colors | F0405030 - Black |








Arrangements Broken Line by Michael Anastassiades , 2018







F0415030 Big Rose-MAX190W

F0416030 Small Rose-MAX70

F0418030 Recessed Rose-MAX190W